

SOPRALASTIC 111

TECHNICAL DATA SHEET
130107CAN1E
(supersedes 080516CAN2E)

DESCRIPTION

SOPRALASTIC 111 is an all season asbestos free SBS modified plastic cement specially designed to be used as a multipurpose sealing compound. It can be used on wet surfaces. Its special formulation, combined with a high level of polymer helps resist flow at high temperature.

SOPRALASTIC 111 is used for caulking and repairing holes and cracks and is a good complement for waterproofing membranes. It is also suitable for metal surfaces.

APPLICATION

SOPRALASTIC 111 must be applied to clean, sound substrates with a trowel.

When repairing cracks or holes **SOPRALASTIC 111** can be used in conjunction with a reinforcement.

Excellent adherence on most materials without primer. **CAN BE APPLIED TO DAMP OR WET SURFACES.**

PROPERTIES

Properties	Standards	SOPRALASTIC 111
Colour	-	Black
Specific gravity at 20 °C (68 °)	-	1.12 kg/L
Solids by weight	-	83 %
Application temperature range – product	-	-10 to 35 °C (32 to 95 °F)
Application temperature range – surface	-	-30 to 35 °C (-22 to 95 °F)
Service temperature range	-	-40 to 85 °C (-40 to 185 °F)
Setting time	-	Between 4 to 24 hours, depending on temperature and quantity applied

(All values are nominal)

PACKAGING

10 kg or 20 kg pails

STORAGE & HANDLING

Shelf life: Up to 36 months in original sealed containers.

Tools can be cleaned with petroleum solvents such as mineral spirits, varsol, xylene, etc.

SOPRALASTIC 111 is a flammable product. Store in a cool, dry area above freezing point. Use in a well ventilated area, far from any open flame. Avoid breathing solvent vapours and prolonged skin contact.

CONSULT THE MATERIAL SAFETY DATA SHEET PRIOR TO USE.

