

SOPRALAP STICK

DESCRIPTION

SOPRALAP STICK is a cover strip composed of SBS modified bitumen and a composite reinforcement. The surface is sanded. The underface is covered with a release protection film.

SURFACE PREPARATION

Using **ELASTOCOL STICK** or **ELASTOCOL STICK ZERO** primer is recommended before the installation of **SOPRALAP STICK** cover strip. Surfaces must be clean, dry and free of loose particles.

INSTALLATION

SELF-ADHESIVE

SOPRALAP STICK is adhered to substrate by peeling off the release protection film. Once installed, a pressure must be applied over the whole surface using a membrane roller to ensure full adhesion.

SOPRALAP STICK is designed to ensure waterproofing of end laps on panels or any other applications requiring the use of a cover strip.

Minimum application temperature: ≥ 0 (32 °F)

FOR COMPLETE INFORMATION ON PRODUCT INSTALLATION, PLEASE CONSULT YOUR SOPREMA REPRESENTATIVE.

PACKAGING

Specifications	SOPRALAP STICK
Thickness	2.5 mm (98.4 mil)
Reinforcement	Composite
Dimensions	0.33 x 12 m (13 in x 39.6 ft)
Roll weight	2.8 kg/m ² (0.6 lb/ft ²)
Surface	Sanded
Underface	Self-adhesive, covered with a release protection film

(All values are nominal)