



SOPRAVAP'R

SELF-ADHESIVE VAPOUR BARRIER MEMBRANE

SOPRAVAP'R is a self-adhesive vapour barrier membrane composed of SBS modified bitumen and resistant to foot traffic. The width of the membrane was designed so that it fits with the top flutes of most steel deck profiles. Thus, the area covered by a roll is optimized and wastage is reduced. SOPRAVAP'R can also be applied at low temperatures.

SURFACE PREPARATION

With the exception of steel decks, all substrates must be primed with ELASTOCOL STICK or ELASTOCOL STICK ZERO. The substrate must be clean, sound, and free of loose materials or contaminants, such as water and grease, which may compromise the adhesion of the product.

SOPRAVAP'R

THICKNESS	0.8 mm
DIMENSIONS	40.8 x 1.14 m (134 x 3.7 ft)
SURFACE	Tri-laminated woven polyethylene
UNDERFACE	Silicone release film

COMPLEMENTARY PRODUCTS

ELASTOCOL STICK and **ELASTOCOL STICK ZERO** primers facilitate the adhesion of the SOPRAVAP'R membranes on all substrates, except steel surfaces.



Thermal barrier not required

Self-sealing properties for mechanically fastened systems

Fast installation

Provides a better fit to steel decks, reducing costs associated with wastage

Since 1908, SOPREMA has specialized in the manufacture of waterproofing products for the construction and civil engineering fields.



1.877.MAMMOUTH
www.soprema.ca

INSTALLATION INSTRUCTIONS

1



Starting at the bottom of the slope, unroll the SOPRAVAP'R membrane to align it, without yet adhering it onto the substrate. Do not immediately remove the silicone release film.

3



Remove one end of the silicone release film and adhere this part of the membrane to the substrate. Remove the remaining release film at a 45° angle to avoid wrinkling the membrane.

5



When the vapour barrier is installed directly on a steel deck, place a thin sheet of metal under the end laps of the vapour barrier.

2



Align the roll parallel to the flutes of the steel deck. Make sure membrane overlaps are supported along their entire length.

4



Overlap adjacent rolls by 75 mm (3 in). End laps must overlap by 150 mm (6 in). Space end laps by at least 300 mm (12 in).

6



The installation is completed.

If you have any questions about this product or its installation, please contact your SOPREMA representative.