

# ELASTOCOL STICK ZERO

TECHNICAL DATA SHEET  
130111SCAN1E  
(supersedes 110204SCAN1E)

## DESCRIPTION

**ELASTOCOL STICK ZERO** is a LEED® compliant (IEQ credit 4.1) primer designed to enhance the adhesion of self-adhesive membranes on various substrates including porous surfaces such as gypsum boards at temperatures above -10 °C (14 °F). It is composed of synthetic polymers, adhesive enhancing resins and solvents.

## APPLICATION

**ELASTOCOL STICK ZERO** can be applied with a brush or a roll. It must be thoroughly dry before applying the waterproofing membrane. **ELASTOCOL STICK ZERO** must be well shaken before use.

**WARNING: Do not accelerate drying of ELASTOCOL STICK ZERO by heating it with a torch.**

Average coverage:            on porous surfaces:            0.2 to 0.4 L/m<sup>2</sup>,  
   on non-porous surfaces:        0.1 to 0.25 L/m<sup>2</sup>.

**FOR COMPLETE INFORMATION ON PRODUCT INSTALLATION, PLEASE CONSULT YOUR SOPREMA REPRESENTATIVE.**

## PROPERTIES

| Properties                           | ELASTOCOL STICK ZERO |
|--------------------------------------|----------------------|
| Specific gravity at 25 °C (77 °F)    | 0.94 kg/L            |
| Color                                | Red                  |
| Solids by Weight                     | 45 %                 |
| Viscosity, Brookfield, 25 °C (77 °F) | 300 - 600 cP         |
| Drying time                          | 30 to 90 minutes     |

(All values are nominal)

## PACKAGING

3.78 L and 19 L pails.

## STORAGE & HANDLING

**Shelf life:** Up to 60 months in original sealed containers, in cool and ventilated area.  
Tools can be cleaned with petroleum solvents such as mineral spirits, varsol and xylene.

## PRECAUTIONS

**ELASTOCOL STICK ZERO** is a flammable product.

Store away from direct sunlight and open flame. Keep ignition sources away during application and until solvent has evaporated. Harmful if inhaled, swallowed or when in contact with the skin. In closed area, ventilate carefully using mechanical means if necessary. Do not pour residues in drains.

**CONSULT THE MATERIAL SAFETY DATE SHEET PRIOR TO USE.**