



1.877.MAMMOUTH www.soprema.ca

TECHNICAL DATA SHEET 130920SCAN2E

(supersedes n/a)

COLOURED QUARTZ AGGREGATES

DESCRIPTION

The **COLOURED QUARTZ AGGREGATES** are used as slip-resistant surface coating when applying liquid **ALSAN RS** membranes and as decorative elements.

COLOURS: COLOURED QUARTZ AGGREGATES are available in a variety of colours. Contact SOPREMA for specific colour selection and availability.

APPLICATION

The COLOURED QUARTZ AGGREGATES must be spread randomly during an ALSAN RS liquid resin wet application (ALSAN RS 233 or 287).

Once the ALSAN RS resin is cured, excess COLOURED QUARTZ AGGREGATES can be removed using a vacuum cleaner, a broom or an oil-free air compressor.

Saturate with a finish coat of ALSAN RS 281 CLEAR FINISH.

FOR COMPLETE INFORMATION ON PRODUCT INSTALLATION, PLEASE CONSULT YOUR SOPREMA REPRESENTATIVE.

PACKAGING

The COLOURED QUARTZ AGGREGATES are packed in a 23 kg (50 lb) bag.

The COLOURED QUARTZ AGGREGATES sizes:

00 : 0.3 - 0.4 mm (30 - 40 mesh) 0 : 0.4 - 0.8 mm (20 - 40 mesh)

DENSITY 2.7- 2.9 kg/m³ (95-105 lb/ft³)

MINERAL HARDNESS Mohs scale: 7

STORAGE & HANDLING

Storage: Always store in a clean and dry location. Product packaging should not be damaged prior to use.



