

SAFETY DATA SHEET

ALSAN TRAFIK HP 515 PART A

Offerte en français



SECTION I: IDENTIFICATION

Soprema USA

310, Quadral Drive

Tel.: 1800 356-3521

<u>Use:</u> Bi-component waterproofing polyurethane primer.

<u>Manufacturer / Distributors</u>:

Soprema Canada Soprema inc.
1675, Haggerty Street 44955, Yale Road West
Drummondville (Quebec) J2C 5P7 Chilliwack (C.-B.) V2R 4H3

Drummondville (Quebec) J2C 5P7 Chilliwack (C.-B.) V2R 4H3 Wadsworth (Ohio) 44281 CANADA CANADA UNITED STATES

Tel.: 604 793-7100

Tel.: 819 478-8163

In case of emergency:

SOPREMA (8:00am to 5:00pm): 1 800 567-1492 CANUTEC (Canada) (24h.): 613 996-6666 CHEMTREC (USA) (24h.): 1 800 424-9300

SECTION II: HAZARD(S) IDENTIFICATION

DANGER

May be fatal if swallowed and enters airways. Harmful if swallowed. May cause respiratory irritation. Causes skin irritation. Causes serious eye irritation. May damage fertility or the unborn child.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not eat, drink or smoke when using this product. Avoid breathing vapours. Use only outdoors or in a well-ventilated area. Wash hands thoroughly after handling. Wear protective gloves, eye protection and an organic vapour respirator. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of container in accordance with local, regional and national regulations.

SECTION III: COMPOSITION AND INFORMATION ON HAZARDOUS INGREDIENTS						
NAME	CAS#	% WEIGHT	EXPOSURE LIMIT (ACGIH)			
			TLV-TWA	TLV-STEL		
Castor oil	8001-79-4	60-100	Not established	Not established		
1-Dodecene	112-41-4	1-5	Not established	Not established		
gamma- Glycidoxypropyltrimethoxysilane	2530-83-8	0.5-1.5	Not established	Not established		
2-Methoxy-1-methylethyl acetate	108-65-6	0.1-1	50 ppm	Not established		

Effects of Short-Term (Acute) Exposure

INHALATION

Castor oil: Castor oil does not form a vapour at room temperature. Therefore, it must be heated or misted before inhalation exposure would occur. Health effects following inhalation exposure are not expected, due to the overall low toxicity of castor oil. There is no human or animal information available. (1)

2-Methoxy-1-methylethyl acetate: High concentrations of vapours may irritate the respiratory system. They can also cause CNS depression (drowsiness, loss of coordination, tiredness). (2)

1-Dodecene and gamma-Glycidoxypropyltrimethoxysilane: No information available.

SKIN CONTACT

Castor oil: Castor oil is not irritating or a mild irritant, based on animal and human information. Application of 50 mL of castor oil, under a patch for 48 hours, was mildly irritating to humans. Castor oil is not expected to produce harmful effects if absorbed through the skin. (1)

1-Dodecene: 1-Dodecene is a moderate skin irritant based on animal information. Prolonged exposure (24 hours) has caused severe irritation. (1)

2-Methoxy-1-methylethyl acetate: Skin contact may probably cause skin irritation. (2)

gamma-Glycidoxypropyltrimethoxysilane: No information available.

EYE CONTACT

Castor oil: Castor oil is not irritating or a mild irritant, based on animal information. It is sometimes used as an eye ointment. (1)

 $\emph{1-Dodecene:}\ 1\text{-Dodecene}$ is probably non-irritant based on animal information. (1)

2-Methoxy-1-methylethyl acetate: Eye contact may probably cause eye irritation. (2)

gamma-Glycidoxypropyltrimethoxysilane: No information available.

Soprema USA

12251 Seaway Road

UNITED STATES

Tel.: 228 701-1900

Gulfport (Mississippi) 39507

INGESTION

Castor oil: Castor oil is not expected to produce significant harmful effects if accidentally ingested, based on animal toxicity information and experience gained through the use of castor oil as a laxative in humans. A single oral dose is considered safe. Ingestion of large doses can cause nausea, vomiting, stomach cramps and diarrhoea. Ingestion is not a typical route of occupational exposure. (1)

2-Methoxy-1-methylethyl acetate: Ingestion may cause irritation to the digestive system. High concentration may cause CNS depression. (2)

I-Dodecene and gamma-Glycidoxypropyltrimethoxysilane: No information available.

Effects of Long-Term (Chronic) Exposure

SKIN SESITIZATION

Castor oil: There is insufficient information available to determine if castor oil is an occupational sensitizer. There are several case reports of dermatitis and occasional facial swelling from the use of lipsticks, where castor oil is believed to be the cause. There is no animal information available. (1)

1-Dodecene, gamma-Glycidoxypropyltrimethoxysilane and 2-Methoxy-1-methylethyl acetate: No information available.

CARCINOGENICITY

Castor oil: There is no human or animal information available. The International Agency for Research on Cancer (IARC) has not evaluated the carcinogenicity of this chemical. The American Conference of Governmental Industrial Hygienists (ACGIH) has no listing for this chemical. The US National Toxicology Program (NTP) has not listed this chemical in its report on carcinogens. (1)

2-Methoxy-1-methylethyl acetate: Has not been identified as probably, possibly or known carcinogenic by IARC. (2)

1-Dodecene and gamma-Glycidoxypropyltrimethoxysilane: No information available.

TERATOGENICITY, EMBRYOTOXICITY, FETOTOXICITY

Castor oil: No human or animal information is available. (1)

2-Methoxy-1-methylethyl acetate: Studies have demonstrated that it is teratogenic in animals and that there is a risk of foetotoxicity. (2)

1-Dodecene and gamma-Glycidoxypropyltrimethoxysilane: No information available.

REPRODUCTIVE TOXICITY

Castor oil: There is no human information available. In the one animal test located, ingestion of castor oil did not cause changes in sperm counts or motility or in the female fertility cycle. (1)

2-Methoxy-1-methylethyl acetate: Studies have demonstrated that it is teratogenic in animals and that there is a risk of foetotoxicity. (2)

1-Dodecene and gamma-Glycidoxypropyltrimethoxysilane: No information available.

MUTAGENICITY

Castor oil: There is no human information available. Castor oil is not expected to be mutagenic. Negative results have been obtained in a test using live animals, in cultured mammalian cells and in bacteria. (1)

1-Dodecene, gamma-Glycidoxypropyltrimethoxysilane and 2-Methoxy-1-methylethyl acetate: No information available.

TOXICOLOGICALLY SYNERGISTIC MATERIALS

Castor oil: No information is available. (1)

1-Dodecene, gamma-Glycidoxypropyltrimethoxysilane and 2-Methoxy-1-methylethyl acetate: No information available.

POTENTIAL FOR ACCUMULATION

Castor oil: Does not accumulate. (1)

1-Dodecene, gamma-Glycidoxypropyltrimethoxysilane and 2-Methoxy-1-methylethyl acetate: No information available.

SECTION IV: FIRST-AID MEASURES

SKIN CONTACT

Wash with plenty of water. If skin irritation occurs: Get medical advice. Take off immediately all contaminated clothing and wash it before reuse.

EYE CONTACT

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice.

INHALATION

Remove person to fresh air and keep comfortable for breathing. Call a poison center if you feel unwell.

SWALLOWING

Immediately call a poison center. Do NOT induce vomiting. Rinse mouth.

SECTION V: FIRE-FIGHTING MEASURES

FLAMMABILITY: Class IIIB (NFPA)

EXPLOSION DATA: Sensitivity to mechanical impact: No.

Sensitivity to static charge: No.

FLASH POINT: 230°C (Castor oil)

AUTO-IGNITION TEMPERATURE: Not available **FLAMMABILITY LIMITS IN AIR:** Not available

FIRE AND EXPLOSION HAZARDS

This product and its vapours are easily ignited by heat, sparks or flames. Vapours may form explosive mixtures with air. Vapours are heavier than air and may travel a considerable distance to a source of ignition and flash back to a leak or open container. The product may ignite on contact with strong oxidizing agents, strong acids and strong bases. Do not cut, puncture or weld empty containers.

COMBUSTION PRODUCTS

Carbon oxides (CO, CO₂) and nitrogen oxides. Irritating and/or toxic gases or fumes may be generated by thermal decomposition or combustion.

FIRE FIGHTING INSTRUCTIONS

Evacuate area. Wear self-contained breathing apparatus and appropriate protective clothing in accordance with standards. Approach fire from upwind and fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Always stay away from containers because of the high risk of explosion. Stop leak before attempting to put out the fire. If leak cannot be stopped, and if there is no risk to the surrounding area, let the fire burn itself out. Move containers from fire area if this can be done without risk. Cool containers with flooding quantities of water until well after fire is out.

MEANS OF EXTINCTION

"Alcohol" foam or polymer foam, dry chemical powder, CO₂, sand. Use of water spray when fighting fire may be inefficient.

SECTION VI: ACCIDENTAL RELEASE MEASURES

RELEASE OR SPILL

Ventilate area. Wear appropriate protective equipment during clean-up. Shut off source of leak if it can be done without risk. Contain the spill. Absorb with inert material such as sand or earth. Sweep or shovel into containers with lids. Cover and remove to appropriate well-ventilated area until disposal. Wash spill area with soap and water. Prevent entry into waterways, sewers or basements. Dispose of this product according to local environmental regulations.

SECTION VII: HANDLING AND STORAGE

HANDLING

Avoid contact with eyes, skin and clothing. Do not ingest. Avoid breathing mist, vapour or dust. Wash thoroughly after handling. Before handling, it is very important that ventilation controls are operating and protective equipment requirements are being followed. People working with this product would be properly trained regarding its hazards and its safe use. Keep away from heat. Tightly reseal all partially used containers. Do not cut, puncture or weld containers.

STORAGE

Store in a cool well-ventilated area out of direct sunlight and away from heat. Store away from incompatible materials. Store the product according to occupational health and safety regulations and fire and building codes. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. Have appropriate fire extinguishers and spill clean-up equipment near storage area. Inspect all containers to make sure they are properly labelled.

SECTION VIII: EXPOSURE CONTROLS / PERSONAL PROTECTION

HANDS: Wear gloves in polyethylene or ethylene vinyl alcohol. For short periods of time, you can use butyl rubber, natural rubber, neoprene rubber, nitrile rubber, polyvinyl alcohol, polyvinyl chloride and Viton.

RESPIRATORY: If the TLV is exceeded, if use is performed in a poorly ventilated confined area, use an approved respirator in accordance with standards (chemical cartridge respirator with organic vapour cartridge(s)).

EYES: Wear chemical safety goggles in accordance with standards.

OTHERS: Eye bath and safety shower.

CONTROL OF VAPOURS: Local exhaust is needed to control vapour and dust level to below recommended limits

Page 2 of 4

SECTION IX: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid **ODOUR AND APPEARANCE:** Clear yellowish with low odour **ODOUR THRESHOLD:** Not available VAPOUR DENSITY (air = 1): Heavier than air **EVAPORATION RATE (Butyl acetate = 1):** Not available **BOILING POINT (760 mm Hg):** Not available FREEZING POINT: Not available SPECIFIC GRAVITY ($H_2O = 1$): 0.959 kg/L**SOLUBILITY IN WATER (20°C):** Not soluble **VOLATILE ORGANIC COMPOUND (V.O.C.):** 0 g/LVISCOSITY: 470 cP (25°C)

SECTION X: STABILITY AND REACTIVITY

STABILITY: This material is stable.

CONDITIONS OF REACTIVITY: Avoid excessive heat.

INCOMPATIBILITY: Strong acids, strong bases, strong oxidizing

agents.

HAZARDOUS DECOMPOSITION PRODUCTS: During a fire, irritating/toxic gases, such as carbon monoxide, carbon dioxide and other toxic may be formed, depending on fire conditions

CONDITIONS TO AVOID: Open flames, heat and prolonged exposure to direct sunlight and moisture.

HAZARDOUS POLYMERISATION: None.

SECTION XI: TOXICOLOGICAL INFORMATION

TOXICOLOGICAL DATA

1-Dodecene: (1)

LC₅₀ (rat): $> 2 100 \text{ mg/m}^3 \text{ (4-hour exposure)}$

 LD_{50} (oral, rat): > 10~000~mg/kg LD_{50} (dermal, rabbit): > 10~000~mg/kg

gamma-Glycidoxypropyltrimethoxysilane: (2)

 LC_{50} (rat): > 5.3 mg/l (4-hour exposure)

 LD_{50} (oral, rat): 8 400 mg/kg LD_{50} (dermal, rabbit): 8 400 mg/kg

2-Methoxy-1-methylethyl acetate: (2)

 LC_{50} (male rat): > 100 ppm (6-hour exposure)

 LD_{50} (oral, rat): > 5 155 mg/kg LD_{50} (dermal, rabbit): > 5 000 mg/kg

Effects of Short-Term (Acute) Exposure

INHALATION

gamma-Glycidoxypropyltrimethoxysilane: May cause irritation to the respiratory tract. (2)

Castor oil, 1-Dodecene, and 2-Methoxy-1-methylethyl acetate: No information available.

EYE IRRITATION

Castor oil: Castor oil is either not irritating or a mild irritant. (1)

1-Dodecene: 1-Dodecene is probably a non-irritant. (1)

gamma-Glycidoxypropyltrimethoxysilane: Causes serious eye damage.
(2)

2-Methoxy-1-methylethyl acetate: Irritating. (2)

SKIN CONTACT

Castor oil: Castor oil is probably not irritating or a mild irritant. (1)

I-Dodecene: 1-Dodecene is a moderate irritant. Prolonged exposure (24 hours) has caused severe irritation. (1)

gamma-Glycidoxypropyltrimethoxysilane: May cause mild skin irritation. (2)

2-Methoxy-1-methylethyl acetate: Slightly irritating. (2)

INGESTION

Castor oil, 1-Dodecene, gamma-Glycidoxypropyltrimethoxysilane and 2-Methoxy-1-methylethyl acetate: No information available.

Effects of Long-Term (Chronic) Exposure

CARCINOGENICITY

Castor oil, 1-Dodecene, gamma-Glycidoxypropyltrimethoxysilane and 2-Methoxy-1-methylethyl acetate: No information available.

TERATOGENOCITY, EMBRYOTOXICITY, FETOTOXICITY

Castor oil, 1-Dodecene, gamma-Glycidoxypropyltrimethoxysilane and 2-Methoxy-1-methylethyl acetate: No information available.

MUTAGENICITY

Castor oil: The available information suggests that castor oil is not mutagenic. (1)

I-Dodecene: Tests on bacterial or mammalian cell cultures did not show mutagenic effects. (2)

gamma-Glycidoxypropyltrimethoxysilane: Not mutagenic. (2)

2-Methoxy-1-methylethyl acetate: No information available. (2)

SKIN SENSITIZATION

1-Dodecene: 1-Dodecene is probably not a skin sensitizer. (1)

Castor oil, gamma-Glycidoxypropyltrimethoxysilane and 2-Methoxy-1-methylethyl acetate: No information available.

REPRODUCTIVE TOXICITY

Castor oil: The limited information available suggests that castor oil is not harmful to reproduction. (1)

1-Dodecene: Animal testing did not show any effects on fertility. (2)

gamma-Glycidoxypropyltrimethoxysilane and 2-Methoxy-1-methylethyl acetate: No information available.

SECTION XII: ECOLOGICAL INFORMATION

ENVIRONMENTAL EFFECTS

Do not allow product or runoff from fire control to enter grounds, basements, storm or sanitary sewers, lakes, rivers, streams or public waterways. Block off drains and ditches. Provincial and federal regulations may require that environmental and / or agencies be notified of a spill incident. Spill area must be cleaned and restored to original condition or to the satisfaction of authorities. May be harmful to aquatic life.

SECTION XIII: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL

This product is considered as dangerous material. Consult local, state, provincial or territory authorities to know disposal methods. This material is also known as dangerous waste by RCRA (USA); disposal should follow EPA regulations.

SECTION XIV: TRANSPORT INFORMATION

Not regulated.

SECTION XV: REGULATORY INFORMATION

DSL: All constituents of this product are included in the Domestic Substances List (DSL – Canada).

TSCA: All constituents of this product are included in the Toxic Substances Control Act Inventory (TSCA – USA).

Prop. 65: This product does not contain chemicals known to the State of California to cause cancer or reproductive toxicity.

SECTION XVI: OTHER INFORMATION

GLOSSARY

ASTM: American Society for Testing and Materials (United

States)

CAS: Chemical Abstract Services

CSA: Canadian Standardization Association
DOT: Department of Transportation (United States)
EPA: Environmental Protection Agency (United States)

GHS Globally Harmonized System

 $\begin{array}{lll} LD_{50}/LC_{50} \colon & \text{Less high lethal dose and lethal concentration published} \\ NIOSH \colon & \text{National Institute for Occupational Safety and Health} \end{array}$

(United States)

RCRA: Resource Conservation and Recovery Act (United States)

TDG: Transportation of Dangerous Goods (Canada)
TLV-TWA: Threshold Limit Value – Time-Weighted Average

Reference:

(1) CHEMINFO (2017) Canadian Centre for Occupational Health and Safety, Hamilton (Ontario) Canada

(2) Manufacturer's SDS

Code of SDS: CA U DRU SS FS 173

For more information: 1 800 567-1492

The Safety Data Sheets of SOPREMA Canada are available on Internet at the following site: www.soprema.ca

Justification of the update:

• Formula.

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.



SAFETY DATA SHEET

ALSAN TRAFIK HP 515 PART B

Offerte en français

GHS	PROTECTIVE CLOTHING	TRANSPORT OF DANGEROUS GOODS	
	PQ C	Not regulated	

SECTION I: IDENTIFICATION

Use: Bi-component waterproofing polyurethane primer.

Manufacturer / Distributors:

Soprema Canada 1675, Haggerty Street Drummondville (Quebec) J2C 5P7

CANADA Tel.: 819 478-8163

In case of emergency: SOPREMA (8:00am to 5:00pm): 1 800 567-1492

Soprema inc. 44955, Yale Road West Chilliwack (C.-B.) V2R 4H3 CANADA

Tel.: 604 793-7100

Soprema USA 310, Quadral Drive Wadsworth (Ohio) 44281 UNITED STATES

Tel.: 1800 356-3521

Soprema USA 12251 Seaway Road Gulfport (Mississippi) 39507

UNITED STATES Tel.: 228 701-1900

CHEMTREC (USA) (24h.): 1 800 424-9300

SECTION II: HAZARD(S) IDENTIFICATION

CANUTEC (Canada) (24h.): 613 996-6666

DANGER

Harmful if swallowed. May be fatal if swallowed and enters airways. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Avoid breathing vapours. Use only outdoors or in a well ventilated area. Wear protective gloves, eye protection and an organic vapour respirator. Contaminated work clothing must not be allowed out of the workplace. Store locked up. Dispose of container in accordance with local, regional and national regulations.

SECTION III: COMPOSITION AND INFORMATION ON HAZARDOUS INGREDIENTS						
NAME	CAS#	% WEIGHT	EXPOSURE LIMIT (ACGIH)			
			TLV-TWA	TLV-STEL		
Methylene diphenyl diisocyanate (MDI)	101-68-8	30-60	0.005 ppm	Not established		
Polymeric diphenylmethane diisocyanate (PMPPI)	9016-87-9	30-60	0.005 ppm	Not established		
Propylene carbonate	108-32-7	10-30	Not established	Not established		

Effects of Short-Term (Acute) Exposure

INHALATION

4,4'-MDI and PMPPI have a very low vapour pressure. Therefore, airborne exposures are unlikely to occur unless they are heated or form an aerosol or mist during pouring, frothing or spraying operations. Shortterm inhalation exposure to isocyanates can cause respiratory and mucous membrane irritation. Symptoms include eye and nose irritation, dry or sore throat, runny nose, shortness of breath, wheezing and laryngitis. Coughing with chest pain or tightness may also occur, frequently at night. These symptoms may occur during exposure or may be delayed several hours. High aerosol concentrations could cause inflammation of the lung tissue (chemical pneumonitis), chemical bronchitis with severe asthmalike wheezing, severe coughing spasms and accumulation of fluid in the lungs (pulmonary oedema), which could prove fatal. Symptoms of pulmonary oedema may not appear until several hours after exposure and are aggravated by physical exertion. (1)

Propylene carbonate: Propylene carbonate does not readily form a vapour at room temperature. Therefore, it must be heated or misted before inhalation exposure would occur. Propylene carbonate is not expected to produce significant harmful effects by this route of exposure, based on limited animal information. There is no human information available. (1)

SKIN CONTACT

4,4'-MDI is a severe skin irritant based on animal information. PMPPI is a severe skin irritant based on information for MDI, a major component of PMPPI. In general, isocyanates can cause skin discolouration (staining) and hardening of the skin after repeated exposures. Skin contact is not expected to result in the absorption of harmful amounts. (1)

Propylene carbonate: Propylene carbonate is a very mild irritant based on animal and human information. It does not readily absorb through the skin. (1)

EYE CONTACT

4,4'-MDI: 4,4'-MDI may cause no irritation or slight eye irritation based on animal information. (1)

PMPPI: PMPPI is a mild eye irritant based on animal information for PMPPI and MDI. (1)

Propylene carbonate: Propylene carbonate is a moderate to severe eye irritant, based on animal information. (1)

INGESTION

There have been no reports of human ingestion of 4,4'-MDI or PMPPI. Animal studies indicate that the toxic effects of the ingestion of 4,4'-MDI and PMPPI are slight. Ingestion could result in irritation and corrosion of the mouth, throat, and digestive tract. Ingestion is not a typical route of occupational exposure. (1)

Propylene carbonate: Propylene carbonate is not expected to be toxic based on animal information. There is no human information available. Ingestion is not a typical route of occupational exposure. (1)

Effects of Long-Term (Chronic) Exposure

LUNGS/RESPIRATORY SYSTEM

Exposure to isocyanates is likely to cause aggravation to individuals with existing respiratory disease, such as chronic bronchitis and emphysema. (1)

RESPIRATORY SENSITIZATION

Respiratory sensitization can develop in people working with 4,4'-MDI and PMPPI or its main component MDI. The sensitization is usually caused by a very large exposure or by multiple exposures. Although varying periods of exposure (1 day to years) may elapse before sensitization occurs, it develops more often during the first few months of exposure. Sensitized individuals react to very low levels of MDI (as low as 0.0014 ppm) that have no effect on unsensitized people. At first, the symptoms may appear to be a cold or mild hay fever. However, severe asthmatic symptoms can develop and include wheezing, chest tightness, shortness of breath, difficulty breathing and/or coughing. Fever, chills, general feelings of discomfort, headache and fatigue can also occur. Symptoms may occur immediately upon exposure, within an hour or several hours after exposure or both and/or at night. Typically the asthma improves with removal from exposure (e.g. weekends and vacations) and returns, in some cases, in the form of an "acute attack" on renewed exposure. Sensitized people who continue to work with isocyanates may develop symptoms sooner after each exposure. The number and severity of symptoms may increase. Following removal from exposure, some workers may continue to have persistent respiratory problems such as asthmatic symptoms, bronchial problems and hypersensitivity to isocyanates. Others may recover fully and may gradually lose their sensitivity within several years. Exposure to isocyanates is likely to cause aggravation to individuals with existing respiratory disease, such as chronic bronchitis and emphysema. Cross-sensitization between different isocyanates may occur. (1)

SKIN SENSITIZATION

Isocyanates are contact sensitizers. Repeated skin contact with 4,4'-MDI and PMPPI may cause skin sensitization in humans. Further skin contact may result in skin inflammation, rash, itching and staining. Allergic contact dermatitis has developed from occupational contact with MDI. (1)

Propylene carbonate: Propylene carbonate did not produce skin sensitization in groups of 50 volunteers tested with 5% and 10% propylene carbonate in water solutions. Sensitization testing with cosmetic products containing propylene carbonate has consistently produced negative results. There is no other human information available. (1)

CARCINOGENICITY

The risk of cancer associated with exposure to isocyanates has been examined in 4 human population studies. No strong association or consistent pattern has been observed. The International Agency for Research on Cancer (IARC) has determined there is inadequate evidence for the carcinogenicity of MDI or polymeric MDI (4,4'-MDI, PMPPI) in humans. There is limited evidence for the carcinogenicity of a mixture containing MDI and polymeric MDI in experimental animals. (1)

4,4'-MDI: IARC has concluded that this chemical is not classifiable as to its carcinogenicity to humans (Group 3). The American Conference of Governmental Industrial Hygienists (ACGIH) has not assigned a carcinogenicity designation to this chemical. The US National Toxicology Program (NTP) has not listed this chemical in its report on carcinogens. (1)

PMPPI: IARC has concluded that this chemical is not classifiable as to its carcinogenicity to humans (Group 3). The ACGIH has no listing for this chemical. The NTP has not listed this chemical in its report on carcinogens. (1)

Propylene carbonate: There is no human information available. A negative result was obtained for dermal exposure to propylene carbonate in an unconfirmed animal study. The IARC has not evaluated the carcinogenicity of this chemical. The ACGIH has no listing for this chemical. The NTP has not listed this chemical in its report on carcinogens.

TERATOGENICITY, EMBRYOTOXICITY, FETOTOXICITY

No human or animal information is available. (1)

REPRODUCTIVE TOXICITY

No human or animal information is available. (1)

MUTAGENICITY

It is not possible to conclude that 4,4'-MDI or PMPPI are mutagenic. No human or animal in vivo studies on 4,4'-MDI and PMPPI have been reported. In one human case report, MDI, a main component of PMPPI, caused DNA damage in white blood cells after inhalation exposure to 5 to 20 ppb. No conclusions can be drawn from this case report. (1)

Propylene carbonate: There is no human information available. Negative results were obtained for propylene carbonate in bacteria and in mammalian cells. An inconclusive result was obtained in one strain of bacteria. (1)

TOXICOLOGICALLY SYNERGISTIC MATERIALS

No information is available. (1)

POTENTIAL FOR ACCUMULATION

4,4'-MDI: 4,4'-MDI can enter the body by inhalation or ingestion. It is probably metabolized to 4,4'-methylene dianiline, which is metabolized further and excreted. (1)

PMPPI: Probably does not accumulate. No information on the breakdown (metabolism) of PMPPI is available. Reacts with water and tissues. MDI is probably metabolized to 4,4'-methylene dianiline, which is further metabolized and excreted. (1)

Propylene carbonate: Probably does not accumulate. (1)

SECTION IV: FIRST-AID MEASURES

SKIN CONTACT

Wash with plenty of water. If skin irritation or rash occurs: Get medical advice. Take off immediately all contaminated clothing and wash it before reuse

EYE CONTACT

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice.

INHALATION

If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a poison center.

SWALLOWING

Immediately call a poison center. Rinse mouth. Do NOT induce vomiting.

SECTION V: FIRE-FIGHTING MEASURES

FLAMMABILITY: Non flammable.

FLASH POINT: 130°C

AUTO-IGNITION TEMPERATURE: > 600°C

FLAMMABILITY LIMITS IN AIR: (% in volume) Not applicable

COMBUSTION PRODUCTS

Carbon oxides (CO, CO₂), nitrogen oxides and hydrogen cyanide.

FIRE FIGHTING INSTRUCTIONS

Evacuate area. Wear self-contained breathing apparatus and appropriate protective clothing in accordance with standards. Approach fire from upwind and fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Always stay away from containers because of the high risk of explosion. Stop leak before attempting to put out the fire. If leak cannot be stopped, and if there is no risk to the surrounding area, let the fire burn itself out. Move containers from fire area if this can be done without risk. Cool containers with flooding quantities of water until well after fire is out.

MEANS OF EXTINCTION

Carbon dioxide, dry chemical powder, protein foam, water spray (for large fires). Alcohol resistant foams are preferred for large fires. General purpose synthetic foams or protein foams may work, but much less effective. Care must be taken since the reaction between water and water-based foam and isocyanates can be vigorous.

SECTION VI: ACCIDENTAL RELEASE MEASURES

RELEASE OR SPILL

Ventilate area. Wear appropriate protective equipment during cleanup. Eliminate all ignition sources. Shut off source of leak if it can be done without risk. Contain the spill. Absorb with inert maternal such as sand or earth. Sweep or shovel into containers with lids, use clean non-sparking tools (e.g. plastic) to collect absorbed material. Cover and remove to appropriate well-ventilated area until disposal. Wash spill area with isocyanates decontaminating solution. Prevent entry into waterways, sewers, basements. Dispose of this product according to local environmental regulations.

SECTION VII: HANDLING AND STORAGE

HANDLING

This product and its vapours are toxic. Avoid contact with eyes, skin and clothing. Do not ingest. Avoid breathing mist, vapour or dust. Wash thoroughly after handling. Before handling, it is very important that ventilation controls are operating and protective equipment requirements are being followed. People working with this product should be properly trained regarding its hazards and its safe use. Keep away from heat. Tightly reseal all partially used containers. Do not cut, puncture or weld empty containers.

STORAGE

Store in a cool well-ventilated area out of direct sunlight and away from heat and ignition sources. Keep storage areas clear of combustible materials. No smoking near storage area. Store away from incompatible materials. Store the product according to occupational health and safety regulations and fire and building codes. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. Have appropriate fire extinguishers and spill clean-up equipment near storage area. Inspect all containers to make sure they are properly labelled.

SECTION VIII: EXPOSURE CONTROLS / PERSONAL PROTECTION

HANDS: Wear polyethylene, ethylene, vinyl alcohol, butyl rubber, natural rubber, neoprene rubber, nitril rubber, polyvinyl alcohol, polyvinyl chloride or Viton gloves.

RESPIRATORY: If the TLV is exceeded, if use is performed in a poorly ventilated confined area, use an approved respirator in accordance with standards.

EYES: Wear chemical safety goggles in accordance with standards.

OTHERS: Eye bath and safety shower.

CONTROL OF VAPOURS: Local exhaust is needed to control vapour and dust level to below recommended limits.

SECTION IX: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid
ODOUR AND APPEARANCE: Brownish-red liquid with slightly
musty odour

ODOUR THRESHOLD: Not available VAPOUR DENSITY (air = 1): 8.5 **EVAPORATION RATE (Butyl acetate = 1):** Not available **BOILING POINT (760 mm Hg):** > 300 °C Not available FREEZING POINT: SPECIFIC GRAVITY $(H_2O = 1)$: 1.22 kg / L**SOLUBILITY IN WATER (20°C):** Not soluble **VOLATILE ORGANIC COMPOUND (V.O.C.):** 0 g/L VISCOSITY: 45 cP (Visco Brookfield LVT)

SECTION X: STABILITY AND REACTIVITY

STABILITY: This material is stable.

INCOMPATIBILITY: Water amines, alcohol, strong acids, strong bases, strong oxidizing agents, amides, phenols, mercaptans, urethanes, ureas and surface active compounds.

HAZARDOUS DECOMPOSITION PRODUCTS: 4,4'-Methylene dianiline (formed by reaction of MDI with water).

CONDITIONS TO AVOID: Moisture, heat, direct sunlight.

HAZARDOUS POLYMERISATION: None.

SECTION XI: TOXICOLOGICAL INFORMATION

TOXICOLOGICAL DATA

4,4'-MDI: (1)

LC₅₀ (rat): 490 mg/m³ (4-hour exposure - aerosol)

 LD_{50} (oral, rat): > 10~000 mg/kg LD_{50} (dermal, rabbit): > 10~000 mg/kg

PMPPI: (1)

LC₅₀ (male rat): 490 mg/m³ (4-hour exposure - aerosol)

LD₅₀ (oral, rat): 10 000 mg/kg LD₅₀ (dermal, rabbit): 6 200 mg/kg

Propylene carbonate: (1)

LC₅₀ (male rat): 5 000 mg/m³ (4-hour exposure)

LD₅₀ (oral, rat): 29 100 mg/kg LD₅₀ (dermal, rabbit): > 26 400 mg/kg

Effects of Short-Term (Acute) Exposure

INHALATION

4,4'-MDI: MDI has a very low vapour pressure and it is difficult to achieve vapour concentrations necessary for inhalation toxicity testing. Therefore, inhalation toxicity studies have focused on the effects of the aerosol. No significant effects were found when rats were exposed to 2, 5 and 15 mg/m³ of MDI aerosol for 6 hours/day, 5 days/week for 2 weeks. (1)

PMPPI: PMPPI has an extremely low vapour pressure and it is difficult to achieve vapour concentrations necessary for inhalation toxicity testing. The desired vapour concentrations can only be obtained by heating the PMPPI source. The vapour evolved readily condenses to an aerosol in the inhalation exposure chambers. Therefore, it is likely that an aerosol rather than a vapour is present. No harmful effects or changes in body weight were observed in rats exposed to PMPPI vapour near the saturation concentration (estimated concentration: 0.2 ppm). (1)

Propylene carbonate: An 8-hour exposure to concentrated vapour of propylene carbonate was not lethal to rats. (1)

EYE IRRITATION

4,4'-MDI: 4,4'-MDI has caused no irritation or slight irritation of the eyes. (1)

PMPPI: PMPPI is a mild eye irritant. (1)

Propylene carbonate: Propylene carbonate is a moderate to severe eye irritant. (1)

SKIN IRRITATION

4,4'-MDI: MDI is a severe skin irritant. (1)

PMPPI: No specific information was located for PMPPI. MDI, a major component of PMPPI, is a severe skin irritant. (1)

Propylene carbonate: Propylene carbonate is a very mild irritant. (1)

INGESTION

4,4'-MDI: Rats were given daily doses of 4.3 to 5 g/kg for 5 days. The only effect was a slight enlargement of the spleen in 2 of 5 rats. (1)

PMPPI: No information available. (1)

Propylene carbonate: Rats orally exposed to a single dose of 5 000 mg/kg propylene carbonate showed salivation, but no other harmful effects. (1)

Effects of Long-Term (Chronic) Exposure

INHALATION

PMPPI: In two studies, six-week old rats were exposed to 0.35, 1.4 or 7.2 mg/m³, or 4.1, 8.4 or 12.3 mg/m³ PMPPI aerosol for 13 weeks. In the first study, a temporary reduction in growth was seen in males and minor cellular changes were observed in the lungs of both sexes at 7.2 mg/m³. In the second study, severe respiratory distress and deaths occurred at 12.3 mg/m³. Less pronounced irritation, increased lung weights and cellular changes in the lungs, but no deaths were observed at 8.4 mg/m³. (1)

4,4'-MDI: No information available. (1)

Propylene carbonate: Rats were exposed to 0, 100, 500, or 1 000 mg/m³/day of propylene carbonate aerosol for 90 days. Blood and urine analysis showed no differences from the control for any of the test groups. The only sign of toxicity observed was some swelling of the eyes at 500 and 1 000 mg/m³/day. There were no effects on behaviour or on motor activity following 6 or 13 weeks of exposure. (1)

RESPIRATORY SENSITIZATION

PMPPI: Mild, but not significant sensitization-like responses occurred in guinea-pigs that inhaled commercial PMPPI at 4.6 mg/m³ for 4 hours/day for 5 days. (1)

4,4'-MDI and propylene carbonate: No information available. (1)

SKIN SENSITIZATION

4,4'-MDI: The sensitizing potency of MDI was investigated using the mouse ear-swelling test (MEST). The dose required to sensitize 50% of the animals was 0.73 mg/kg. In this test, MDI was less potent than hexamethylene diisocyanate (HDI) and dicyclohexylmethane diisocyanate (HMDI), but more sensitizing than toluene diisocyanate (TDI). Cross reactivity was observed between MDI and HDI, HMDI and TDI. (1)

PMPPI: Commercial PMPPI caused skin sensitization in guinea-pigs that had previously inhaled MDI. The degree of sensitization appeared to be greater for PMPPI than for MDI. (1)

Propylene carbonate: Propylene carbonate did not show skin sensitization in guinea pigs. (1)

CARCINOGENICITY

4,4'-MDI: There is no animal information on the carcinogenicity of MDI itself. In one study, polymeric MDI containing 44.8-50.2% monomeric MDI was tested for carcinogenicity by inhalation in rats. An increased incidence of lung tumours was observed. IARC has determined there is limited evidence for the carcinogenicity of a mixture containing monomeric and polymeric MDI to experimental animals. (1)

PMPPI: Rats were exposed to 0.2, 1.0 or 6.0 mg/m³ respirable PMPPI aerosol for up to 24 months (6 hours/day, 5 days/week). Indicators of recurrent lung tissue damage were seen at 1.0 and 6.0 mg/m³. An increase in the incidence of lung cancer was also observed at 6.0 mg/m³. It was concluded that exposure to PMPPI at concentrations leading to recurrent lung damage was associated with the development of pulmonary tumours. IARC has concluded there is limited evidence for the carcinogenicity of a mixture containing MDI and PMPPI in experimental animals. (1)

Propylene carbonate: A negative result was obtained for mice exposed dermally to 50microL, two times/week for 104 weeks. (1)

MUTAGENICITY

4,4'-MDI: It is not possible to conclude that MDI is mutagenic. (1)

PMPPI: No information available. (1)

Propylene carbonate: The available information does not indicate that propylene carbonate is mutagenic. (1)

SECTION XII: ECOLOGICAL INFORMATION

ENVIRONMENTAL EFFECTS

Do not allow product or runoff from fire control to enter grounds, basements storm or sanitary sewers, lakes, rivers, streams, or public waterways. Block off drains and ditches. Provincial and federal regulations may require that environmental and / or other agencies be notified of a spill incident. Spill area must be cleaned and restored to original condition or to the satisfaction of authorities. May be harmful to aquatic life.

SECTION XIII: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL

This product is considered as dangerous material. Consult local, state, provincial or territory authorities to know disposal methods. This material is also known as dangerous waste by RCRA (USA); disposal should follow EPA regulations.

SECTION XIV: TRANSPORT INFORMATION

This product is not regulated by DOT and TDG.

SECTION XV: REGULATORY INFORMATION

DSL: All constituents of this product are included on the Domestic Substances List (DSL – Canada)

TSCA: All constituents of this product are included on the Toxic Substances Control Act Inventory (TSCA – USA).

Prop. 65: This product does not contain chemicals known to the State of California to cause cancer or reproductive toxicity.

SECTION XVI: OTHER INFORMATION

GLOSSARY

ASTM: American Society for Testing and Materials (United States)

CAS: Chemical Abstract Services

CSA: Canadian Standardization Association
DOT: Department of Transportation (United States)
EPA: Environmental Protection Agency (United States)

GHS Globally Harmonized System

LD₅₀/LC₅₀: Less high lethal dose and lethal concentration published NIOSH: National Institute for Occupational Safety and Health

(United States)

RCRA: Resource Conservation and Recovery Act (United States)

TDG: Transportation of Dangerous Goods (Canada)
TLV-TWA: Threshold Limit Value – Time-Weighted Average

Reference:

 CHEMINFO (2015) Canadian Centre of Occupational Health and Safety, Hamilton (Ontario) Canada.

Code of SDS: CA U DRU SS FS 173 For more information: 1 800 567-1492

The Safety Data Sheets of SOPREMA Canada are available on Internet at the following site: www.soprema.ca

Justification of the update:

GHS format.

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.