

NATURAL QUARTZ AGGREGATES

DESCRIPTION

The **NATURAL QUARTZ AGGREGATES** are used as slip-resistant surface coating when applying liquid **ALSAN RS** membranes.

COLOUR: Natural quartz.

APPLICATION

The **NATURAL QUARTZ AGGREGATES** must be spread randomly during an **ALSAN RS** liquid resin wet application.

Once the **ALSAN RS** resin is cured, excess **NATURAL QUARTZ AGGREGATES** can be removed using a vacuum cleaner, a broom or an oil-free air compressor.

Saturate with a finish coat of **ALSAN RS 287 COLOR FINISH BASE**.

FOR COMPLETE INFORMATION ON PRODUCT INSTALLATION, PLEASE CONSULT YOUR SOPREMA REPRESENTATIVE.

PACKAGING

The **NATURAL QUARTZ AGGREGATES** are packed in a 23 kg (50 lb) bag, except for size no.2, which is offered in 45 kg (100 lb) bags.

The **NATURAL QUARTZ AGGREGATES** sizes:

0: 0.4 - 0.8 mm (20 - 40 mesh)

1: 0.7 - 1.2 mm (16 - 30 mesh)

2: 1.0 - 1.6 mm (10 - 16 mesh)

DENSITY

1521-1600 kg/m³ (95-100 lb/ft³)

MINERAL HARDNESS

Mohs scale: 6 - 8

STORAGE & HANDLING

Storage: Always store in a clean and dry location. Product packaging should not be damaged prior to use.