



WATERPROOFING

# LASTOBOND® SHIELD ROOFS



## SELF-ADHESIVE ROOF UNDERLAYMENT MEMBRANE



LASTOBOND SHIELD is a self-adhesive roofing underlayment membrane composed of SBS modified bitumen and a nonslip tri-laminated woven polyethylene.

- Quick, easy-to-remove silicone release film
- Self-sealing
- Nonslip
- High tensile strength
- 100% UV protected

### SURFACE PREPARATION

The use of a primer is not required when the membrane is covered within 24 hours. The use of a primer greatly enhances the bonding strength of self-adhesive membranes. The roof covering should be installed as soon as possible following the installation of the membrane.

LASTOBOND SHIELD	
DIMENSIONS	22.9 x 0.91 m (75 x 3 ft)
SURFACE	Tri-laminated woven polyethylene
UNDERFACE	Split-release silicone paper
GROSS AREA	20.8 m <sup>2</sup>
NET AREA	19.1 m <sup>2</sup>

## INSTALLATION INSTRUCTIONS

1



Roll out approximately 3 m (10 ft) of membrane. Align the roll and adhere the first metre (3 ft) in place.

2



Unroll the membrane as far as possible.

3



Once the LASTOBOND SHIELD is in place, fold back half the membrane and peel off the silicone release film diagonally while holding the membrane tight.

4



Once the silicone release film has been peeled back, adhere the membrane to the substrate.

5



Repeat with the second half.

6



The roof valley is protected.

If you have any questions about this product or its installation, please contact your SOPREMA representative.



SOPREMA.CA

1 877 MAMMOUTH