



ACCESSORY PRODUCT

APPLICATIONS

WALLS

SOPRASEAL LT ADDITIVE

TECHNICAL DATA SHEET 180319SCANE

(supersedes 151202SCANE)

DESCRIPTION

SOPRASEAL LT ADDITIVE is a liquid additive designed to be used with SOPRASEAL LM 202 VP, SOPRASEAL LM 203 and SOPRASEAL LM BLOCK FILLER.

SOPRASEAL LT ADDITIVE must be blended with one of the above-mentioned products and will enable application of these products at temperatures as low as -4°C (25°F).

APPLICATION

Ensure that the substrate is free of frost and condensation. Follow all application directions for SOPRASEAL LM 202 VP, SOPRASEAL LM 203 or SOPRASEAL LM BLOCK FILLER.

Minimum application temperature: 4°C (40°F) and higher. To apply SOPRASEAL LM 202 VP, SOPRASEAL LM 203 or SOPRASEAL LM BLOCK FILLER at temperatures below 4°C (40°F), but above -4°C (25°F), blend 1 entire quart container of SOPRASEAL LT ADDITIVE.

Ambient and substrate temperatures must remain at or above -4°C (25°F) until the material has dried. Protect the material from precipitation for a minimum of 24 hours.

Drying time will vary depending on ambient and substrate temperatures, humidity, and the ability of the substrate to absorb water.

FOR COMPLETE INFORMATION ON PRODUCT INSTALLATION, PLEASE CONSULT YOUR SOPREMA REPRESENTATIVE.

PACKAGING

8 x 0.95 L (1 quart) plastic bottles per carton.

STORAGE AND HANDLING

Shelf life: Approximately 24 months, properly stored in original unopened containers. Protect from freezing temperatures, extreme heat and direct sunlight.

For more information, refer to the instructions on the container label and relevant safety data sheet (SDS).

