



COMPLEMENTARY PRODUCTS

APPLICATIONS

PARKING DECKS

ALSAN ACCELERATOR

TECHNICAL DATA SHEET 160517SCANE

(supersedes 100309SCAN2E)

DESCRIPTION

ALSAN TRAFIK HP traffic coating system is a polyurethane membrane designed to waterproof vehicular and pedestrian traffic areas on concrete decks. It can also be installed on plywood decks for balconies. This system is composed of three products for light pedestrian traffic and of four products for vehicular traffic. ALSAN ACCELERATOR is added to ALSAN TRAFIK HP 520 to accelerate drying.

APPLICATION

ALSAN ACCELERATOR is supplied in 100 ml cans. For ordering purposes, for every pallet of ALSAN TRAFIK HP 520 (36x 19 L cans), two boxes of ALSAN ACCELERATOR (18 cans per box) should be ordered.

ALSAN ACCELERATOR is used exclusively with ALSAN TRAFIK HP 520 and should not be combined with any other ALSAN product

ALSAN ACCELERATOR is supplied in 100 ml cans. For ordering purposes, for every pallet of ALSAN TRAFIK HP 520 (36 x 19 L cans), two boxes of ALSAN ACCELERATOR (18 cans per box) should be ordered.

RESTRICTION

Always use caution when handling the products. Do not smoke. Keep away from open flame, fire or any ignition source. Avoid skin and eye contact with this product. Cured product may be disposed of in standard landfills. Uncured product is considered a hazardous material and must be handled as such, in accordance with local, provincial, and federal regulations.

FOR COMPLETE INFORMATION ON PRODUCT INSTALLATION, PLEASE CONSULT YOUR SOPREMA REPRESENTATIVE.

PACKAGING

Specifications	ALSAN ACCELERATOR
Physical state	Liquid
Colour (Color)	Clear, yellow
Specific gravity @ 25°C	1.030 - 1.060 kg/L
Brookfield viscosity @ 25°C	30 - 60 cP
Solidification point	< 0°C

(All values are nominal)

STORAGE AND HANDLING

Shelf life: 12 months in original unopened container.

Always store closed containers in cool, ventilated and dry location away from heat and oxidizing agents. Do not store in direct sunlight or in temperatures above 25 °C.

KEEP FROM FREEZING.

For more information, refer to the instructions on the container label and relevant safety data sheet (SDS).



SOPREMA.US • 1.800.356.3521

SOPREMA.CA • 1.877.MAMMOUTH

TDS_ALSAN_ACCELERATOR.indd