



APPLICATIONS

ROOFS

TECHNICAL DATA SHEET 181002SCANF

(supersedes 150629SCANF)

DESCRIPTION

ALSAN ALL-PURPOSE CLEANER is a water-based detergent designed to dissolve, remove grease and accumulations of dirt, oil and grease without the use of harsh solvents on surfaces to be recovered by R NOVA PLUS.

Moreover, ALSAN ALL-PURPOSE CLEANER is used to reactivate surfaces of the R NOVA PLUS membranes exposed for more than seven (7) days to environment elements and contaminants.

APPLICATION

ALSAN ALL-PURPOSE CLEANER is applied using rolls, brushes, mop or low pressure sprayer.

When work is interrupted and the surface of the cured resin is exposed to environment elements, thoroughly clean the in-place and cured resin with ALSAN ALL-PURPOSE CLEANER. Apply and allow ALSAN ALL-PURPOSE CLEANER to remain 5 to 10 minutes. Do not allow the surface to dry. Rince the surface thoroughly and entirely with clean water. Allow the surface to dry completely before covering the surface. Make sure to do an adhesion test patch before the application of the first coat of R NOVA PLUS.

Temperature application: 5 to 35 °C (41 to 95 °F).

FOR COMPLETE INFORMATION ON PRODUCT APPLICATION, PLEASE CONSULT YOUR SOPREMA REPRESENTATIVE.

PACKAGING

Specifications	ALSAN ALL-PURPOSE CLEANER
Physical state	Liquid
Colour	Clear
Container	18.9 L (5.0 US Gal)
Coverage rate per container	139 m² (1500 ft²)

CLEANING

Tools can be cleaned with soap and water.

STORAGE AND HANDLING

Storage: Up to 24 months in original sealed container, protected from moisture. Store in a ventilated place, away from heat and direct sunlight.

For more information, refer to instructions on the container label and relevant safety data sheet (SDS).





