

## ALSAN RS COLOR ADDITIVE

TECHNICAL DATA SHEET  
140730SCAN1E  
(supersedes 130502SCAN3E)

### DESCRIPTION

**ALSAN RS COLOR ADDITIVE** is a coloured additive to be added to a polymethyl methacrylate-based (PMMA) clear liquid resin **ALSAN RS 287 COLOR FINISH BASE** and **ALSAN RS 289 TEXTURED BASE**.

COLOURS: **ALSAN RS COLOR ADDITIVE** is available in assorted standard colours (refer to sample 25006):

Traffic WHITE, Light Grey, Pebble Grey, Window Grey, Stone Grey, Beige, Terracotta.

						
White Traffic Product Code 25011	Light Grey Product Code 25012	Pebble Grey Product Code 21104	Window Grey Product Code 25009	Stone Grey Product Code 25013	Beige Product Code 25014	Terracotta Product Code 25998
RAL 9016	RAL 7035	RAL 7032	RAL 7040	RAL 7030	RAL 1001	RAL 8023

\*\*\*Additional colours are available upon special order. Please consult your SOPREMA representative.

### SURFACE PREPARATION

Surfaces must be dry, clean and free of loose particles, formwork, curing products, irregularities, slurry, etc.

### APPLICATION

**MIXING:** Coloured additives **ALSAN RS COLOR ADDITIVE** must be mixed prior being added to the liquid resin.

Using a slow-speed (200 to 400 rpm) mechanical agitator, thoroughly mix the entire container of colour additive into the **ALSAN RS 287 COLOR FINISH BASE** or **ALSAN RS 289 TEXTURED BASE** resin for two minutes before each use. Those should be thoroughly mixed prior to application. Prepared colour resin can then be poured off into smaller containers for smaller batch mixing. Catalyze with **ALSAN RS CATALYST** only the amount of material that can be used within 10-15 minutes. Add pre-measured catalyst **ALSAN RS CATALYST** to the resin component, stir for two minutes and apply to substrate.

**APPLICATION:** After mixing, apply resin to clean and prepared substrate at the required consumption using rollers, brushes or notched squeegee. The resin should be spread evenly onto the surface. See individual system specifications for specific guidelines regarding application of primer, membrane, topcoat and/or slip-resistant protective surfacing.

### PACKAGING

**ALSAN RS COLOR ADDITIVE** is supplied in a 1.5-kg can.

### STORAGE & HANDLING

**Shelf life:** 12 months, properly stored in original unopened containers. For more information, refer to instruction on the label of the can and to relevant Material Safety Data Sheet (MSDS).