

# ELASTOCOL 350

TECHNICAL DATA SHEET 190827SCANE

(supersedes 101220SCANE)



ACCESSORIES PRODUCTS

APPLICATIONS

ROOFS

## DESCRIPTION

**ELASTOCOL 350** is a stabilised bituminous emulsion (water based). It is used as a primer for waterproofing membranes, to enhance adhesion of torch-applied and self-adhesive membranes (**SOPRASOLIN**, **COLPHENE**, **SOPRASEAL STICK**, etc.) on most surfaces. It should be used in areas where solvent-based primers are not recommended.

## APPLICATION

**ELASTOCOL 350** can be applied by brush, roller or spray gun (the Airless process is not suitable) on wood decks, concrete, metal, bituminous systems, asphalt, etc.

Allow to dry completely before application of the membrane. Self-adhesive membranes should be applied the same day as the application of **ELASTOCOL 350**.

Minimum Application Temperature: 5 °C (41 °F).

FOR COMPLETE INFORMATION ON PRODUCT INSTALLATION, PLEASE CONSULT YOUR SOPREMA REPRESENTATIVE.

## PACKAGING

Specifications	ELASTOCOL 350
Colour	Dark Brown
Specific Gravity at 20 °C (68 °F)	1.00 kg/L
Format	19 L (5 US Gallon)
Coverage per container*	76 to 127 m <sup>2</sup> (828 to 1 383 ft <sup>2</sup> )

\*The coverage rate is approximate and may vary depending on the the substrate condition and the application technique.  
(All values are nominal)

## PROPERTIES

Properties	Standards	ELASTOCOL 350
Solids by Weight	-	44 %
Viscosity, Ford cup n°4, 20 °C (68 °F)	-	64 s
Drying time	-	Between 1 to 12 hours, depending on temperature and quantity applied.

(All values are nominal)

## CLEANING

Tools can be cleaned with petroleum solvents such as mineral spirits, varsol, xylene, etc.

## STORAGE & HANDLING

**Shelf life:** Up to 24 months in original sealed containers.

Storage temperature: 5 to 40 °C (41 to 104 °F). Do not freeze.

**ELASTOCOL 350** is not ruled by hazardous materials transport regulations.

For more information, refer to the instructions on the container label and relevant safety data sheet (SDS).



SOPREMA.US • 1.800.356.3521

SOPREMA.CA • 1.877.MAMMOUTH

NOTE : All products manufactured by SOPREMA Inc. comply with the description and properties indicated in the technical data sheet that was current at the date of manufacture.

TDS\_ELASTOCOL\_350.indd

# ELASTOCOL

## 350

TECHNICAL DATA SHEET 190827SCANE

(supersedes 101220SCANE)



ACCESSORIES PRODUCTS

APPLICATIONS

ROOFS

## PROPERTIES

Properties	Standards	PRODUCT NAME

(All values are nominal)

## CLEANING

Mauris hendrerit euismod pulvinar. Sed a nibh vitae dui eleifend placerat quis at metus. Nunc sit amet leo enim. Sed nibh risus, hendrerit a consequat sed, aliquet sed felis. Fusce blandit iaculis mattis. Ut quis sapien vitae turpis pharetra consectetur quis sit amet mi. Cras facilisis odio quis erat iaculis et ullamcorper tortor pretium.

## STORAGE AND HANDLING

Pellentesque sollicitudin consequat libero non fringilla. Maecenas blandit risus a neque pretium ultrices. Proin porta, nisi non vulputate volutpat, odio odio mollis erat, sit amet auctor nibh est nec neque.

For more information, refer to the instructions on the container label and relevant safety data sheet (SDS). (METTRE LA NOTE POUR LES PRODUITS LIQUIDES OU DANGEREUX).



SOPREMA.US • 1.800.356.3521

SOPREMA.CA • 1.877.MAMMOUTH

NOTE : All products manufactured by SOPREMA Inc. comply with the description and properties indicated in the technical data sheet that was current at the date of manufacture.

TDS\_ELASTOCOL\_350.indd

2/x