



DESCRIPTION

ELASTOCOL STICK is a primer designed to enhance the adhesion of self-adhesive membranes on porous surfaces such as “**DENS GLASS GOLD**” and “**DENS DECK**” at temperatures above $-10\text{ }^{\circ}\text{C}$ ($14\text{ }^{\circ}\text{F}$). It is composed of SBS synthetic rubbers, adhesive enhancing resins and volatile solvents. It is also suitable to prime non-porous surfaces such as concrete, fibre cement, metal, and wood.

APPLICATION

ELASTOCOL STICK can be applied with a brush, a roll or a spray can. It must be thoroughly dry before applying the waterproofing membrane. **ELASTOCOL STICK** must be shaken well before use.

WARNING: DO NOT ACCELERATE DRYING OF ELASTOCOL STICK BY HEATING IT WITH A TORCH.

FOR COMPLETE INFORMATION ON PRODUCT INSTALLATION, PLEASE CONSULT YOUR SOPREMA REPRESENTATIVE.

COVERAGE

Average coverage: porous surfaces: 0.3 to 0.5 L/m²,
non-porous surfaces: 0.1 to 0.25 L/m².

PROPERTIES

Properties	ELASTOCOL STICK
Specific Gravity at 20 °C	0.79 kg/L
Colour	Red
Solids by Weight	24 %
Viscosity, Brookfield at 25 °C	200 cP
Drying time	15 to 60 minutes, depending on temperature and quantity applied.

(All values are nominal)

PACKAGING

3.78 L, 19 L pails and 350 g spray cans.

STORAGE & HANDLING

Shelf life: Up to 60 months in original sealed containers, in cool and ventilated area.

Tools can be cleaned with petroleum solvents such as mineral spirits, varsol, xylene, etc.

Store in a well ventilated area. Keep away from any source of heat, dampness, humidity, oxidizing agents or direct sunlight. Flammable before curing. Keep away from sources of ignition.

For more information, refer to instruction on the label of the can and to relevant Material Safety Data Sheet (MSDS).



ELASTOCOL



ELASTOCOL STICK

TECHNICAL DATA SHEET ANZ-TDS-15-ELASTOCOL STICK



WATERPROOFING
COMPLEMENTARY PRODUCTS

APPLICATIONS

PRIMER

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this publication is based on the present state of our best knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by Commonwealth or State Legislation. The owner, their representative or the contractor is responsible for checking the suitability of products for their intended use.

Note: Field service where provided, does not constitute supervisory responsibility. Suggestions made by Soprema Australia Pty Ltd either verbally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not Soprema Australia Pty Ltd are responsible for carrying out procedures appropriate to a specific application.

DOCUMENT CONTROL	
Product	ALSAN FLASHING
Initial Issue	29.06.2016
Amendment	03.07.2019
Author	SB

