

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 05/10/2017 Revision date: 05/10/2017

SECTION 1: Identification of the sub	ostance/mixture and of the company/undertaking
1.1. Product identifier	
Product form	: Mixture
Product name	: DUOTACK® SPF Adhesive Part B (System 20)
1.2. Relevant identified uses of the sub-	stance or mixture and uses advised against
Use of the substance/mixture	: Low pressure Polyurethane Foam Adhesive, Side B Component, for PROFESSIONAL USE ONLY
1.3. Details of the supplier of the safety	data sheet
Manufacturer: SOPREMA INC. 310 Quadral Dr. Wadsworth, OH 44281 Tel: 1-800-356-3521	
Distributors: SOPREMA Canada 1675 Haggerty Street Drummondville (Quebec) J2C 5P7 Tel: 1-819-478-8163	
SOPREMA Canada 44955 Yale Road West Chilliwack (BC) V2R 4H3 CANADA Tel: 1-604-793-7100	
SOPREMA USA 12251 Seaway Road Gulfport (Mississippi) 39507 UNITED STATES Tel: 1-228-701-1900	
1.4. Emergency telephone number	
Emergency number	: CHEMTREC 1-800-434-9300 (Acct.# CCN20515). CANUTEC 1-613-996-6666
SECTION 2: Hazards identification	
2.1. Classification of the substance or r	nixture
Classification (GHS-US)	
Skin Sens. 1 H317	
Full text of H statements : see section 16	
2.2. Label elements	
GHS-US labeling	
Hazard pictograms (GHS-US)	GHS07
Signal word (GHS-US)	: Warning
Hazard statements (GHS-US)	: H317 - May cause an allergic skin reaction
Precautionary statements (GHS-US)	<ul> <li>P261 - Avoid breathing dust, fume, gas, mist, spray, vapors</li> <li>P272 - Contaminated work clothing must not be allowed out of the workplace</li> <li>P280 - Wear nitrile gloves</li> <li>P302+P352 - If on skin: Wash with plenty of water</li> <li>P321 - Specific treatment (see a doctor on this label)</li> <li>P333+P313 - If skin irritation or rash occurs: Get medical advice/attention</li> <li>P363 - Wash contaminated clothing before reuse</li> <li>P501 - Dispace of containing the pace drapes with local regional or patienal regulations</li> </ul>

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## 2.3. Other hazards

## No additional information available

## 2.4. Unknown acute toxicity (GHS US)

No data available

## **SECTION 3: Composition/information on ingredients**

3.1. Substance

## Not applicable

dibutyltin dilaurate	(0.4.0.14.) 77 50 7		Classification (GHS-US)
	(CAS No) 77-58-7	< 0.24	Skin Corr. 1C, H314 Skin Sens. 1, H317 Muta. 2, H341 STOT SE 1, H370 STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Non-hazardous components	n/a	99.76-100	n/a

		advice (show the label where possible).
First-aid measures after inhalation	:	Assure fresh air breathing. Allow the victim to rest.
First-aid measures after skin contact		Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Wash with plenty of soap and water. If skin irritation or rash occurs: Wash immediately with lots of water, Remove clothing while washing. Get medical advice/attention. Specific treatment (see Wash skin with plenty of water on this label). Wash contaminated clothing before reuse.
First-aid measures after eye contact	:	Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.
First-aid measures after ingestion	:	Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.
4.2. Most important symptoms and effects	s,	both acute and delayed
Symptoms/injuries after inhalation	:	May cause an allergic skin reaction.
Symptoms/injuries after skin contact	:	May cause an allergic skin reaction.
Symptoms/injuries after eye contact	:	No data available.
Symptoms/injuries after ingestion	:	Harmful if swallowed.
Symptoms/injuries upon intravenous administration	:	No effects known.
Chronic symptoms	:	No effects known.

### 4.3. Indication of any immediate medical attention and special treatment needed

### No additional information available

SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray.
Unsuitable extinguishing media	: Do not use a heavy water stream.
5.2. Special hazards arising from the sul	ostance or mixture
Explosion hazard	: Contains gas under pressure; may explode if heated.
Reactivity	: On burning: release of irritant gases/vapours (carbon monoxide - carbon dioxide).
5.3. Advice for firefighters	
Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

according to Federal Register / vol. 77, No. 56 / Monday, P		
SECTION 6: Accidental release measures		
6.1. Personal precautions, protective equ	ipment and emergency procedures	
General measures	: Evacuate area.	
6.1.1. For non-emergency personnel		
Emergency procedures	: Evacuate unnecessary personnel.	
6.1.2. For emergency responders		
Protective equipment	: Equip cleanup crew with proper protection.	
Emergency procedures	: Ventilate area.	
5 7 1		
6.2. Environmental precautions	authorition if liquid enters accurs or public uptors. Drevent poil and uptor pollution	
	authorities if liquid enters sewers or public waters. Prevent soil and water pollution.	
6.3. Methods and material for containment		
Methods for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.	
6.4. Reference to other sections		
See Heading 8. Exposure controls and personal p	protection.	
SECTION 7: Handling and storage		
SECTION 7: Handling and storage           7.1.         Precautions for safe handling		
	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Avoid breathing dust, fume, gas, mist, spray, vapors.	
7.1. Precautions for safe handling	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation	
7.1.         Precautions for safe handling           Precautions for safe handling	<ul> <li>Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Avoid breathing dust, fume, gas, mist, spray, vapors.</li> <li>Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.</li> </ul>	
7.1.       Precautions for safe handling         Precautions for safe handling         Hygiene measures	<ul> <li>Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Avoid breathing dust, fume, gas, mist, spray, vapors.</li> <li>Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.</li> </ul>	
<ul> <li>7.1. Precautions for safe handling</li> <li>Precautions for safe handling</li> <li>Hygiene measures</li> <li>7.2. Conditions for safe storage, including</li> </ul>	<ul> <li>Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Avoid breathing dust, fume, gas, mist, spray, vapors.</li> <li>Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.</li> <li>g any incompatibilities</li> <li>Keep only in the original container in a cool, well ventilated place away from : Do not expose to temperatures exceeding 50 °C/ 122 °F, Keep away from heat, hot surfaces, sparks, open</li> </ul>	
<ul> <li>7.1. Precautions for safe handling</li> <li>Precautions for safe handling</li> <li>Hygiene measures</li> <li>7.2. Conditions for safe storage, includin Storage conditions</li> </ul>	<ul> <li>Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Avoid breathing dust, fume, gas, mist, spray, vapors.</li> <li>Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.</li> <li>g any incompatibilities</li> <li>Keep only in the original container in a cool, well ventilated place away from : Do not expose to temperatures exceeding 50 °C/ 122 °F, Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container closed when not in use.</li> </ul>	
<ul> <li>7.1. Precautions for safe handling</li> <li>Precautions for safe handling</li> <li>Hygiene measures</li> <li>7.2. Conditions for safe storage, includint</li> <li>Storage conditions</li> <li>Incompatible products</li> </ul>	<ul> <li>Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Avoid breathing dust, fume, gas, mist, spray, vapors.</li> <li>Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.</li> <li>g any incompatibilities</li> <li>Keep only in the original container in a cool, well ventilated place away from : Do not expose to temperatures exceeding 50 °C/ 122 °F, Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container closed when not in use.</li> <li>Strong bases. Strong acids.</li> </ul>	
<ul> <li>7.1. Precautions for safe handling</li> <li>Precautions for safe handling</li> <li>Hygiene measures</li> <li>7.2. Conditions for safe storage, including</li> <li>Storage conditions</li> <li>Incompatible products</li> <li>Incompatible materials</li> </ul>	<ul> <li>Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Avoid breathing dust, fume, gas, mist, spray, vapors.</li> <li>Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.</li> <li>g any incompatibilities</li> <li>Keep only in the original container in a cool, well ventilated place away from : Do not expose to temperatures exceeding 50 °C/ 122 °F, Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container closed when not in use.</li> <li>Strong bases. Strong acids.</li> <li>Sources of ignition. Direct sunlight.</li> </ul>	
<ul> <li>7.1. Precautions for safe handling</li> <li>Precautions for safe handling</li> <li>Hygiene measures</li> <li>7.2. Conditions for safe storage, including</li> <li>Storage conditions</li> <li>Incompatible products</li> <li>Incompatible materials</li> <li>Storage temperature</li> </ul>	<ul> <li>Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Avoid breathing dust, fume, gas, mist, spray, vapors.</li> <li>Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.</li> <li>g any incompatibilities</li> <li>Keep only in the original container in a cool, well ventilated place away from : Do not expose to temperatures exceeding 50 °C/ 122 °F, Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container closed when not in use.</li> <li>Strong bases. Strong acids.</li> <li>Sources of ignition. Direct sunlight.</li> <li>&lt;= 35 °C</li> </ul>	

SECTION 8: Exposure c	ontrols/personal protection	
8.1. Control parameters		
dibutyltin dilaurate (77-58-7)		
USA ACGIH	ACGIH TWA (mg/m³)	0.1 mg/m³ (Tin organic compounds, as Sn; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
USA ACGIH	ACGIH STEL (mg/m <sup>3</sup> )	0.2 mg/m³ (Tin organic compounds, as Sn; USA; Short time value; TLV - Adopted Value)
8.2. Exposure controls		
Appropriate engineering controls	Ensure good ventilation of the we	ork station.
Personal protective equipment	: Avoid all unnecessary exposure.	
Hand protection	: Wear nitrile gloves protective glo	oves.
Eye protection	: Chemical goggles or safety glass	ses.
Skin and body protection	: Protective clothing.	
Respiratory protection	: In case of insufficient ventilation,	wear suitable respiratory equipment.
Other information	: Do not eat, drink or smoke during	g use.

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>SECTION 9: Physical and chemical</b>	properties
9.1. Information on basic physical and	I chemical properties
Physical state	: Liquid
Appearance	: Liquid.
Color	: Off-white
Odor	: slight
Odor threshold	: No data available
рН	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: >= 93.3 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: ≈ 0.59 mPa
Relative vapor density at 20 °C	: No data available
Specific Gravity	: ≈1.1
Solubility	: Moderately soluble in water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available
9.2. Other information	

VOC content

: < 5 g/l calculated per SCAQMD rule 443.1 when mixed with Part A

SECTION 10: Stability and reactivity	
10.1. Reactivity	
On burning: release of irritant gases/vapours (carb	on monoxide - carbon dioxide).
10.2. Chemical stability	
Stable under normal conditions.	
10.3. Possibility of hazardous reactions	
Not established.	
10.4. Conditions to avoid	
Extremely high or low temperatures.	
10.5. Incompatible materials	
Strong acids. Strong bases.	
10.6. Hazardous decomposition products	
fume. Carbon monoxide. Carbon dioxide.	
<b>SECTION 11: Toxicological informatio</b>	n
11.1. Information on toxicological effects	
Acute toxicity :	Not classified
dibutyltin dilaurate (77-58-7)	
LD50 oral rat	2071 mg/kg body weight (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rat	> 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

dibutyltin dilaurate (77-58-7)	
ATE US (oral)	2071.000 mg/kg body weight
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation	: May cause an allergic skin reaction.
Symptoms/injuries after skin contact	: May cause an allergic skin reaction.
Symptoms/injuries after eye contact	: No data available.
Symptoms/injuries after ingestion	: Harmful if swallowed.
Symptoms/injuries upon intravenous administration	: No effects known.
Chronic symptoms	: No effects known.
Other information	: Likely routes of exposure: inhalation.

# **SECTION 12: Ecological information**

dibutyltin dilaurate (77-58-7)	
Threshold limit algae 1	> 1 mg/l (EC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Scenedesmus subspicatus; Static system; Fresh water; Experimental value)
12.2. Persistence and degradability	
DUOTACK® SPF Adhesive Part B	
Persistence and degradability	Not established.
dibutyltin dilaurate (77-58-7)	
Persistence and degradability	Not readily biodegradable in water. No (test)data on mobility of the substance available. Not established.
12.3. Bioaccumulative potential	
DUOTACK® SPF Adhesive Part B	
Bioaccumulative potential	Not established.
dibutyltin dilaurate (77-58-7)	
BCF fish 1	31 - 813 (BCF; OECD 305: Bioconcentration: Flow-Through Fish Test; 7 days; Carassius carassius; Flow-through system; Fresh water; Experimental value)
Bioaccumulative potential	Potential for bioaccumulation ( $500 \le BCF \le 5000$ ). Not established.
12.4. Mobility in soil	
Ale a dell'Alement la ferma e l'encontra la bite	

No additional information available

12.5.	Other adverse effects	
Effect on ozone layer		:
Effect on the global warming		: No known ecological damage caused by this product.
Other information		: Avoid release to the environment.

SECTION 13: Disposal considerations				
13.1. Waste treatment methods				
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Dispose of container in accordance with local, regional or national regulations.			

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ecology - waste materials	: Avoid release to the environment.			
SECTION 14: Transport information				
In accordance with DOT				
Transport document description	: UN3500 Chemical under pressure, n.o.s., 2.2			
UN-No.(DOT)	: 3500			
DOT NA no.	: UN3500			
DOT Proper Shipping Name	: Chemical under pressure, n.o.s.			
Technical name	: (1,1,1,2 Tetrafluoroethane, Nitrogen)			
Class (DOT)	: 2.2 - Class 2.2 - Non-flammable compressed gas 49 CFR 173.115			
Hazard labels (DOT)	: 2.2 - Non-flammable gas			
	2			
DOT Symbols	: G - Identifies PSN requiring a technical name			
DOT Special Provisions (49 CFR 172.102)	: T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the applicable liquefied compressed gases are authorized to be transported in portable tanks in accordance with the requirements of 173.313 of this subchapter			
DOT Packaging Exceptions (49 CFR 173.xxx)	: None			
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 335			
DOT Packaging Bulk (49 CFR 173.xxx)	: 313;315			
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 75 kg			
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 150 kg			
DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded			
Additional information				
Emergency Response Guide (ERG) Number	: 126			
Other information	: No supplementary information available.			
ADR				
Transport document description				
Transport by sea				
UN-No. (IMDG)	: 3500			
Proper Shipping Name (IMDG)	: CHEMICAL UNDER PRESSURE, N.O.S.			
Class (IMDG)	: 2 - Gases			
Air transport				
UN-No.(IATA)	: 3500			
Proper Shipping Name (IATA)	: Chemical under pressure, n.o.s.			
Class (IATA)	: 2			
SECTION 15: Regulatory information				
15.1. US Federal regulations				
DUOTACK® SPF Adhesive Part B				
Not listed on the United States TSCA (Toxic Substances Control Act) inventory				
15.2. International regulations				

15.2. International regulations

## CANADA

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### **EU-Regulations**

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

### Classification according to Directive 67/548/EEC or 1999/45/EC

Not classified

### 15.2.2. National regulations

No additional information available

## 15.3. US State regulations

DUOTACK® SPF Adhesive Part B		
U.S California - Proposition 65 - Carcinogens List	No	
U.S California - Proposition 65 - Developmental Toxicity	No	
U.S California - Proposition 65 - Reproductive Toxicity - Female	No	
U.S California - Proposition 65 - Reproductive Toxicity - Male	No	

dibutyltin dilaurate (77-58-7)							
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)			
No	No	No	No				

### SECTION 16: Other information

: 05/10/2017

Other information

: None.

#### Full text of H-phrases::

H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H341	Suspected of causing genetic defects
H370	Causes damage to organs
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

NFPA health hazard

NFPA fire hazard

NFPA reactivity

: 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was

given.

: 1 - Must be preheated before ignition can occur.

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



### **HMIS III Rating**

SDS US (GHS HazCom 2012) - Custom

This SDS contains all the information required by ANSI Z400.1 standard (United States), by regulation 29 CFR Part 1910-1200 of the Hazard Communication Standard of OSHA and is in accordance with DORS/88-66 of WHMIS (Canada).

The best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herin, we cannot guarantee that these are the only hazards that exist.