

SENTINEL

PVC MOLDED UNIVERSAL CORNERS

TECHNICAL DATA SHEET 190617SCANE

(supersedes -)



ACCESSORY PRODUCTS

APPLICATIONS

ROOFS

DESCRIPTION

SENTINEL PVC MOLDED UNIVERSAL CORNERS are injection molded circular membrane pieces, composed of unreinforced thermoplastic polyvinyl chloride (PVC). They are used as reinforcement for irregular details. **SENTINEL PVC MOLDED UNIVERSAL CORNERS** are available in white.

INSTALLATION

SENTINEL PVC MOLDED UNIVERSAL CORNERS are welded to the area requiring reinforcement using an electric hot air welder.

FOR COMPLETE INFORMATION ON PRODUCT INSTALLATION, PLEASE CONSULT YOUR SOPREMA REPRESENTATIVE.

PACKAGING

Specifications	SENTINEL PVC MOLDED UNIVERSAL CORNERS
Thickness	1.7 mm (70 mil)
Diameter	177.8 mm (7 in)
Underface	Bare-backed
Qty/box	20

(All values are nominal)

STORAGE AND HANDLING

SENTINEL PVC MOLDED UNIVERSAL CORNERS should be stored in a clean and dry location, away from heat and moisture, on a pallet covered with tarps if needed.



SOPREMA.US • 1.800.356.3521

SOPREMA.CA • 1.877.MAMMOUTH

NOTE: All products manufactured by SOPREMA Inc. comply with the description and properties indicated in the technical data sheet that was current at the date of manufacture.

TDS_SENTINEL_PVC_MOLDED_UNIVERSAL_CORNERS.indd