

# SENTINEL T-JOINT PATCHES

TECHNICAL DATA SHEET 200513SCANE

(supersedes 190617SCANE)



ACCESSORY PRODUCTS

APPLICATIONS

ROOFS

## DESCRIPTION

**SENTINEL T-JOINT PATCHES** are pieces of circular membrane composed of thermoplastic polyvinyl chloride (PVC) and a fiberglass reinforcement. They are specially design to be installed on **SENTINEL T-joints** membranes. **SENTINEL T-JOINT PATCHES** are available in white and grey.

## INSTALLATION

**SENTINEL T-JOINT PATCHES** are welded to the PVC membrane, on every T-joints, using an electric hot air welder. The **SENTINEL T-JOINT PATCHES** can also be used as reinforcement wherever needed.

FOR COMPLETE INFORMATION ON PRODUCT INSTALLATION, PLEASE CONSULT YOUR SOPREMA REPRESENTATIVE.

## PACKAGING

Specifications	SENTINEL T-JOINT PATCHES
Thickness	1.5 mm (60 mil)
Reinforcement	Glass fiber
Diameter	114 mm (4.5 in)
Underface	Bare-backed
Qty/pal	100

(All values are nominal)

## STORAGE AND HANDLING

**SENTINEL T-JOINT PATCHES** should be stored in a clean and dry location, away from heat and moisture, on a pallet covered with tarps if needed.



SOPREMA.US • 1.800.356.3521

SOPREMA.CA • 1.877.MAMMOUTH

NOTE : All products manufactured by SOPREMA Inc. comply with the description and properties indicated in the technical data sheet that was current at the date of manufacture.