

SENTINEL VCM

TECHNICAL DATA SHEET 201019SCANE

(supersedes -)



ACCESSORY PRODUCTS

APPLICATIONS

ROOFS

DESCRIPTION

SENTINEL VCM is a 24 gauge (0.6 mm) galvanized metal sheet with a 20 mil SENTINEL PVC membrane laminated to one side. SENTINEL VCM is also available in 24 gauge (0.6 mm) Stainless Steel or 0.04" Aluminum by special order.

SENTINEL VCM can be used to fabricate metal flashings, pitch-pans and edge details. It allows the user to create effective methods in detailing PVC-to-metal transitions.

INSTALLATION

SENTINEL VCM can be used in both mechanically fastened and adhered roofing systems.

FOR COMPLETE INFORMATION ON PRODUCT INSTALLATION, PLEASE CONSULT YOUR SOPREMA REPRESENTATIVE.

PACKAGING

Specifications	SENTINEL VCM
Colors	White and grey*
Dimensions	1.2 x 3.0 m (4 x 10 ft)
Coverage	3.7 m ² (40 ft ²)
Qty/pal	10

*Grey is available on special order only
(All values are nominal)

STORAGE AND HANDLING

All materials must be stored in a clean, dry location and cover as necessary to protect from environmental damage such as extreme cold, heat or moisture. Monitor varying environmental conditions during storage, handling and applications.



SOPREMA.US • 1.800.356.3521

SOPREMA.CA • 1.877.MAMMOUTH

NOTE: All products manufactured by SOPREMA Inc. comply with the description and properties indicated in the technical data sheet that was current at the date of manufacture.