



COMPLEMENTARY PRODUCTS

APPLICATIONS

WALLS

SOPRASEAL STICK PRIMER

TECHNICAL DATA SHEET 151014SCANE

(supersedes 151008SCANE)

DESCRIPTION

SOPRASEAL STICK PRIMER is a primer specifically designed to enhance the adhesion of self-adhesive SOPRASEAL wall membranes on porous surfaces such as exterior gypsum boards at temperatures above - 30°C (-22°F). It is composed of SBS synthetic rubbers, adhesive enhancing resins and volatil solvents.

RECOMMENDED SUBSTRATES

This product can be used on exterior gypsum boards, wood, metal and concrete.

APPLICATION

SOPRASEAL STICK PRIMER can be applied with a brush or a roll on dry and clean substrates. It must be thoroughly dry before applying the waterproofing membrane. SOPRASEAL STICK PRIMER must be well shaken before use.

WARNING: KEEP AWAY FROM ALL FLAME OR SPARK SOURCES WHEN SOPRASEAL STICK PRIMER IS DRYING.

FOR COMPLETE INFORMATION ON PRODUCT APPLICATION, PLEASE CONSULT YOUR SOPREMA REPRESENTATIVE.

PACKAGING

Specifications	SOPRASEAL STICK PRIMER
Physical state	Liquid
Colour	Orange
Specific gravity at 20°C (68°F)	0.79 kg/L
Solids by weight	24%
Viscosity, Brookfield at 25°C (77°F)	200 cP
Coverage per 19 L pail	porous surfaces 0.3 à 0.5 L/m ² non-porous 0.1 à 0.25 L/m ²
Drying time	15 to 60 minutes, depending on temperature and quacity applied

(All values are nominal)

STORAGE AND HANDLING

Shelf life: Up to 60 months in original sealed containers, in cool and ventilated area.

Tools can be cleaned with petroleum solvents such as mineral sprits, varsol, xylene, etc.

Store in a well ventilated area. Keep away from any source of heat, dampness, humidity, oxidizing agents or direct sunlight. Flammable before curing. Keep away from sources of ignition.

For more information, refer to instructions on the container label and relevant safety data sheet (SDS).



SOPREMA.US • 1.800.356.3521

SOPREMA.CA • 1.877.MAMMOUTH

TDS_SOPRASEAL_STICK_PRIMER.indd