

SOPRALASTIC 123

TECHNICAL DATA SHEET
130109SCAN3E
(supersedes 080515CAN1E)

DESCRIPTION

SOPRALASTIC 123 is a black waterproofing coating composed of elastomeric bitumen, mineral fillers and solvents. **SOPRALASTIC 123** is used to revitalize existing roofs in order to offer a better protection and to prolong their service life. It may be used on asphalt roofs and metal surfaces. It must be protected in all cases, either by a coat of **SOPRALASTIC 124 ALU** or small gravel.

APPLICATION

- Carefully clean and dry the surface.
- Cut open and repair blisters.
- If used over an old dry surface, **ELASTOCOL 500** primer is recommended before applying **SOPRALASTIC 123**. Spread **ELASTOCOL 500** (about 0.25 L/m²).
- To repair cracks, spread a first layer of **SOPRALASTIC 123** and cover with a reinforcement fabric strip soaked in **SOPRALASTIC 123** using a trowel.
- Spread **SOPRALASTIC 123** using a brush or a squeegee at 0.5 L/m². Cover **SOPRALASTIC 123** with mineral protection, or a coat of **SOPRALASTIC 124 ALU** at 0.2 to 0.3 L/m².

PROPERTIES

Properties	Standards	SOPRALASTIC 123
Specific gravity at 20 °C (68 °F)	-	1.12 kg/L
Color	-	Black
Solids by Weight	-	72 %
Resistance to frost	-	Good
Resistance to UV light	-	Poor
Drying time	-	24 hours, depending on temperature and quantity applied.

(All values are nominal)

PACKAGING

19 L pails

STORAGE & HANDLING

Shelf life: Up to 36 months in original sealed containers.

Tools can be cleaned with petroleum solvents such as mineral spirits, varsol, xylene, etc.

SOPRALASTIC 123 is a highly flammable product.

Store away from direct sunlight and open flame. Keep ignition sources away during application and until solvent has evaporated. Harmful if inhaled, swallowed or when in contact with skin. In closed areas, ventilate carefully using mechanical means if necessary. Do not pour residues in drains.

CONSULT THE MATERIAL SAFETY DATA SHEET PRIOR TO USE.

