



SOPREMA Inc.
 Technical Department
 1640 Haggerty Street
 Drummondville, Quebec J2C 5P8
 Phone: 819-478-2400
 866-478-2400
 Fax: 819-478-8051
 Web Site: www.soprema.ca

TECHNICAL BULLETIN

No.: **0107CE**
 DATE ISSUED: February 2007
 REPLACES: 0105CE

Relates to:	✓	Roofing Systems
	✓	Air Barrier
		Civil Engineering Waterproofing
	✓	Sopranature

Subject: GlasRoc™ Sheathing

Related subject: Air/Vapour Barrier

Substrate for Self-Adhesive Applications

GlasRoc™ Sheathing is an acceptable substrate for the application of self-adhesive air/vapour barrier membranes. GlasRoc™ Sheathing needs to be primed with ELASTOCOL STICK primer prior to the application of self-adhesive membranes.

SOPREMA general recommendations regarding surface preparation and membrane installation (including temperature limitations) apply to these boards and remain unchanged.

Substrate for Heat-Welded Applications

GlasRoc™ Sheathing is not acceptable by SOPREMA for any heat-welded membrane installation.

GlasRoc is a registered trademark of BPB Canada Inc.

- END OF TECHNICAL BULLETIN -

Note: This technical bulletin was prepared by SOPREMA Inc. for architects, engineers, building owners, and contractors, as a reference guide in designing, selecting and constructing roofing, and/or waterproofing and/or air/vapour barriers utilizing Soprema Inc. products. SOPREMA Inc. reserves the right to change, or modify, at our discretion, without prior notice, any information, recommendations, or specifications contained in this technical bulletin.