

SOPRA-CELLULOSE

THERMAL AND ACOUSTICAL CELLULOSE INSULATION FOR INTERIOR AND EXTERIOR WALLS, ATTICS, FLOORS AND CEILINGS.

COVERAGE CHART (ATTIC)

THERMAL RESISTANCE		APPLIED THICKNESS		THICKNESS AFTER SETTLING		MASS PER UNIT AREA		COVERAGE PER BAG		MINIMUM BAGS PER UNIT AREA	
RSI	R	mm	in	mm	in	kg/m ²	lb/ft ²	m ²	ft ²	100 m ²	1000 ft ²
2.1	12	94	3.7	84	3.3	2.0	0.42	5.54	59.7	18.0	16.8
2.3	13	103	4.0	92	3.6	2.2	0.46	5.06	54.5	19.8	18.4
3.4	19	152	6.0	135	5.3	3.3	0.68	3.42	36.9	29.2	27.1
3.5	20	156	6.1	139	5.5	3.4	0.70	3.33	35.8	30.1	27.9
3.9	22	174	6.9	155	6.1	3.8	0.78	2.99	32.1	33.5	31.1
5.3	30	237	9.3	211	8.3	5.2	1.06	2.20	23.6	45.5	42.3
5.6	32	250	9.8	223	8.8	5.5	1.12	2.08	22.4	48.1	44.7
6.7	38	299	11.8	267	10.5	6.5	1.34	1.74	18.7	57.6	53.5
7.0	40	312	12.3	279	11.0	6.8	1.40	1.66	17.9	60.1	55.9
8.6	49	384	15.1	343	13.5	8.4	1.72	1.35	14.6	73.9	68.6
8.8	50	393	15.5	351	13.8	8.6	1.76	1.32	14.2	75.6	70.2
10.8	61	482	19.0	430	16.9	10.5	2.16	1.08	11.6	92.8	86.2

Settled density 24.5 kg/m³ (1.5 lb/ft³). This chart indicates the minimum number of bags to use. The final result will vary according to the application technique, the equipment, and the hose used. From R-40 or RSI-7.0, it may be necessary to make an adjustment according to the application technique.

INFORMATIONS

ADDRESS	DAY / MONTH / YEAR	NAME OF APPLICATOR
	DATE OF APPLICATION	
	THICKNESS INSTALLED	SIGNATURE

CUSTOMER SERVICE

Professionals SOPREMA.CA • 1.877.MAMMOUTH

Residential 1.877.478.8408

