



COMPLEMENTARY PRODUCTS

APPLICATIONS

ROOFS

FOUNDATIONS

PLAZA DECKS

SOPRADRAIN 10-G

TECHNICAL DATA SHEET APTDS-E-63-01

DESCRIPTION

SOPRADRAIN 10-G is a high-strength drainage panel consisting of a polypropylene core with a factory-laminated geotextile for installation over waterproofing membranes in most vertical and horizontal commercial drainage applications.

Reduced structural loading: **SOPRADRAIN 10-G** weighs less than 1 kg/m² compared to 145 kg/m² for a 10 cm drainage layer of gravel.

Reduced thickness: **SOPRADRAIN 10-G** is only 1 cm thick compared to 10 cm for gravel drainage, allowing better clearance at doors and a reduction in heights of upstands and curbs.

INSTALLATION

When used in below grade applications always install **SOPRADRAIN 10-G** filter fabric towards backfill.

FOR COMPLETE INFORMATION ON PRODUCT INSTALLATION, PLEASE CONSULT YOUR SOPREMA REPRESENTATIVE.

PROPERTIES

Drainage Core	Standards	SOPRADRAIN 10-G
Roll Dimensions	-	1.83 m x 15.25 m
Gross Coverage	-	27.9 m ²
Thickness	-	10 mm
Compressive Strength	ASTM D 1621	550 kPa
Maximum In-Plane Flow Rate	ASTM D 4716 (Hydraulic gradient of 1)	223 L/min•m

(All values are nominal)

Geotextile Properties	Standards	SOPRADRAIN 10-G
Apparent Opening Size	ASTM D 4751	0.21 mm
Water Flow Rate	ASTM D 4491	5690 L/min•m ²
Grab Tensile	ASTM D 4632	450 N
Grab Elongation	ASTM D 4632	50 %
Puncture Resistance	ASTM D 4833	300 N

(All values are nominal)

