

RESISTO

PLASTIC CEMENT ULTRA

MASTIC



A superior plastic cement developed specifically for professional roofers. With a high concentration of bitumen, it seals roof elements such as flashing, vents or upstands and is use to repair various joints, holes and cracks, built-up roofing, etc.

- Application on all surfaces with optimum bonding
- Excellent resistance to temperature variations
- Use without primer

PRODUCT PURPOSE

Application	Waterproofing complement	
Building Part	Roofing	Foundations
	Walls	Other
Substrates	Wood	Asphalt shingles
	Concrete	Metal

PRODUCT CHARACTERISTICS

Installation Method	Extruder	Trowel
Operating Temperature	-40 °C to 80 °C (-40 °F to 176 °F)	

PACKAGING

Code	Containers	Quantity per Pallet
53017	300 ml (10 oz)	1200
53019	4 kg (2.2 lb)	120
53023	13.6 kg (30 lb)	48
53022	20 kg (44 lb)	36

PROPERTIES

Properties	PLASTIC CEMENT ULTRA
Color	Black
Solids by Weight	86%
Flow	None at these temperatures

All values are nominal)

PLASTIC CEMENT ULTRA

INSTALLATION

Storage	Two years in its original closed packaging, in a cool, well-ventilated area. Store in a cool, dry place up to 40 °C (104 °F). The product can withstand freezing.
Minimum Application Temperature	0 °C (32 °F)
Tools Required	 Extruder  Trowel
Surface Preparation	The substrate must be clean and free of dust, grease or other contaminants.
Installation	Apply with a trowel or an extruder.
Drying time	Between 4 and 24 hours, depending on ambient temperature and the amount applied.
Recommendations/ Limitations	Do not apply strips greater than 1 cm (1/2 in) in width. It is not recommended to use a product containing bitumen directly on softwood boards or on flexible polyvinyl chloride.
Warnings	Keep out of the reach of children. Properly close the container after each use. Keep out of the sun and away from ignition sources. During use, keep away from ignition sources. No smoking. After application, keep away from flames until solvent has evaporated. Do not pour residues in drains.

