

# LAP STICK

## COVER STRIP

Cover strip which seals cross-section overlap of support panels Duoboard.

- Excellent dimensional stability
- Excellent tear resistance

### PRODUCT PURPOSE

Application	Waterproofing
Building Part	Roofing
Types of Slope	Negative slope with internal drain
	Outside low slope
Type of Coating	Bitumen membrane

### PRODUCT CHARACTERISTICS




Technology	SBS modified bitumen
Surface	Sand
Underface	Silicone release film
Reinforcement	High performance composite
Installation Method	Self-adhesive
Maximum exposure	Cover as soon as possible

### PACKAGING

Code	Width		Length		Thickness		Net Area		Brute Area		Quantity (per pallet)
	m	in	m	ft	mm	mils	m <sup>2</sup>	ft <sup>2</sup>	m <sup>2</sup>	ft <sup>2</sup>	
04088	0.33	13	12	39.37	2.5	98	3.96	42.63	3.96	42.63	90

## LAP STICK

### INSTALLATION

Storage	If the products are stored outdoors, cover them with an opaque protective cover after removing the delivery packaging. Can withstand freezing but should be reactivated to at least 10° C (50° F), 24 hours before installation.		
Minimum Application Temperature	0 °C (32 °F)		
Required Products	ELASTOCOL STICK	<b>OR</b> EXTERIOR PRIMER	
Tools required	 Tape measure	 Smoothing roller	
	 Knife		
Surface Preparation	The substrate must be clean, dry and free of dust, grease or other contaminants.		
Installation	<ol style="list-style-type: none"> <li>1. Prime the substrate with ELASTOCOL STICK or EXTERIOR PRIMER.</li> <li>2. Adhere to the support by removing the silicone release film.</li> <li>3. Apply pressure to the entire surface with a smoothing roller to ensure good adhesion.</li> </ol>		
Recommendations/ Limitations	It is not recommended to use a product containing bitumen directly on softwood boards or flexible polyvinyl chloride.		