

ACOUSTIDRAIN

SOUNDPROOFING PRODUCT FOR DRAINPIPE

RESISTOSOUND SOUNDPROOFING PRODUCT LINE

ADVANTAGES

- > Fast and easy to install
- > No special tools
- > ACOUSTIDRAIN comes in a kit with everything you need to soundproof pipes and elbows.
- > NO MORE TOILET FLUSHING NOISE.

Acoustidrain is a revolutionary acoustic product that eliminates the noise caused by water flowing in indoor sanitary drainage or fall pipes.



ACOUSTIDRAIN is a revolutionary acoustic product that eliminates the noise caused by water flowing in indoor sanitary drainage or fall pipes. ACOUSTIDRAIN is self-adhesive and also has a self-adhesive closure. With ACOUSTIDRAIN, you no longer need to use heavy and costly cast-iron pipes as an alternative to PVC or ABS pipes. This means that plumbing installation is easier, quicker and cheaper.

A solution from



Soundproofing products

ACOUSTIDRAIN

SOUNDPROOFING PRODUCT FOR DRAINPIPE

SOUND TESTING

The tests were conducted on-site.

MEASUREMENT CONDITIONS	LEVEL MEASURED IN DB(A)
Plastic pipe without insulation	54
Plastic pipe with mineral wool	39
Plastic pipe with ACOUSTIDRAIN	< than 26
Cast-iron pipe without insulation	52
Cast-iron pipe with ACOUSTIDRAIN	< than 26

dB(A) results are presented for information purposes only. Equivalent performance cannot be guaranteed by Soprema inc.

These results show that non-insulated cast-iron pipes do not resolve noise problems as effectively as ABS or PVC pipes insulated solely with mineral wool.

It should be noted that for each 3 dB(A) reduction, acoustic effectiveness is doubled. Thus, a dB(A) reading of 26 compared with 39 translates into soundproofing that is 16 TIMES MORE EFFECTIVE.

For comparison purposes, piping unaccompanied by an acoustic product and boxed out with a 5/8 in gypsum wall results approximately in a 34 dB(A) reading when measured 1 ft from the wall.

fig.1





fig.2




ACOUSTIDRAIN

SOUNDPROOFING PRODUCT FOR DRAINPIPE

RESISTOSOUND SOUNDPROOFING PRODUCT LINE

fig.3



CHARACTERISTICS


- Thickness:** Approximately 14 mm ($\frac{7}{16}$ in.)
Size: 99 cm x 40 cm (39 in. x 15 $\frac{3}{4}$ in.)
Weight: Approximately 5.8 kg/m² (1.2 PSF)
Note: An ACOUSTIDRAIN sheet covers 99 linear cm (39 in.) of 75 mm (3 in.) diameter piping.

ACOUSTIDRAIN comes in a handy kit containing:

- 5 pieces measuring 99 linear cm (39 in.) of the ACOUSTIDRAIN product
- 2 pieces of ACOUSTIDRAIN foam for elbows
- 21 24-inch Tie-Wraps

Note: Although the kits are designed for pipes measuring 3 in in diameter, there are extensions for 4 in pipes.

fig.4



INSTALLATION GUIDE

- 1 Slide the product vertically behind the pipe to be soundproofed by pressing on the jointing or on a previously installed section of ACOUSTIDRAIN to ensure the product is straight and to facilitate closure of the joint (fig. 1).
- 2 Next, remove the pre-cut section of the silicone film to the opposite side of the overlapping joint of the ACOUSTIDRAIN product (fig. 2 and 3).
- 3 After removing the silicone film, stick that section onto the pipe (fig. 4).
- 4 The opposite side (the overlapping joint) is treated the same way, by cutting the silicone film as closely as possible to the pipe (fig. 5).

fig.5



**PEACE OF MIND
RELAXING
COMFORT
PEACEFUL HOME**

A solution from
**RESISTO
SOUND®**
Soundproofing products

ACOUSTIDRAIN

SOUNDPROOFING PRODUCT FOR DRAINPIPE

INSTALLATION GUIDE (CONTINUE)

- 5 Close off the overlapping joint by first removing the silicone film from the overlapping section (fig. 6) then closing the previously affixed self-adhesive joint of the ACOUSTIDRAIN product (fig. 7).
- 6 The overlapping joint is then kept sealed using the tie-wraps provided in the kit. Place one at each end, as well as one at the centre, about 49.5 cm (19½ in.) from the ends. Close the joints between the sections with duct tape (fig. 8).
- 7 Next treat the elbows using 32 cm x 49.5 cm (12¾ in. x 19½ in.) pieces of foam with the black film supplied in the kit. The 32-cm section should be placed perpendicular to the elbows and then wrapped around the elbows in such a way as to overlap.

It is secured using tie-wraps supplied in the kit; there should be one in the centre and one at each end. Take care to place the black film on the outside.

The foam piece must also overlap the previously installed ACOUSTIDRAIN product (fig. 9).

For a more aesthetically pleasing installation, the excess pieces of foam can be trimmed at right angles so they don't stick out (fig. 10).




fig.6




fig.7



fig.8



fig.10



fig.9

1640 Haggerty, Drummondville (Québec) J2C 5P8

Phone: 819.478.8408 | Fax: 819.478.0199

CUSTOMER SERVICE: 1.877.478.8408

www.resisto.ca

AR322



SOPREMA

