

SOPRA-XPS 20

TECHNICAL DATA SHEET 190903SCANE

(supersedes 190805SCANE)



INSULATION

APPLICATIONS

WALLS

DESCRIPTION

SOPRA-XPS 20 is a rigid thermal insulation board made of extruded polystyrene composed of closed cell foam.

SOPRA-XPS 20 is mainly used as thermal insulation for above grade **SOPREMA** wall systems and on the inside of foundation walls. It can also be used for residential applications on exterior foundation walls and under concrete slabs.

SOPRA-XPS 20 is available in four edges treatment :

- Boards with butt edges on four sides
- Boards with shiplap edges on two sides
- Boards with shiplap edges on four sides
- Boards with slotted on two sides. In this way, when one panel is installed next to another one, it's creating the necessary space for a wood furring strip of 19 x 64 mm (1 x 3 in). This option is used for above-grade exterior walls and on the inside of foundation walls.

SOPRA-XPS 20 does not have any CFC and HCFC - Zero ozone depletion potential.

Minimum 25 % post-consumer and post industrial recycled content.

SOPRA-XPS 20 meets GREENGUARD GOLD certification.

INSTALLATION

MECHANICALLY ATTACHED

Install insulation boards using fasteners and 50 mm (2") diameter washers.

When another layer of **SOPRA-XPS 20** insulation is required, it should be installed with staggered joints on the first layer.

A 100 mm (4 in) **SOPRASEAL STICK FLASHPRO HT** or **ALL WEATHER FLASHING TAPE** self-adhering membrane strip can then be installed centered on panel joints.

Maximum service temperature: 75 °C (167 °F).

RESTRICTIONS

- **SOPRA-XPS 20** is installed where the applied loads do not exceed 20 psi.
- **SOPRA-XPS 20** is a combustible product. To comply with the National Building Code, it must be used in combination with a thermal barrier.
- **SOPRA-XPS 20** can not be used in a wall assembly with a combustible veneer.

FOR COMPLETE INFORMATION ON PRODUCT INSTALLATION, PLEASE CONSULT YOUR SOPREMA REPRESENTATIVE.



SOPREMA.US • 1.800.356.3521

SOPREMA.CA • 1.877.MAMMOUTH

NOTE : All products manufactured by SOPREMA Inc. comply with the description and properties indicated in the technical data sheet that was current at the date of manufacture.

TDS_SOPRA-XPS_20.indd

SOPRA-XPS 20



INSULATION



APPLICATIONS

WALLS

TECHNICAL DATA SHEET 190903SCANE

(supersedes 190805SCANE)

PACKAGING

SPECIFICATIONS	SOPRA-XPS 20	
	BOARD DIMENSIONS*	BOARD THICKNESSES*
Shi lap on 2 edges (length)	2438 mm x 1220 mm (8 ft x 4 ft)	25 mm (1 in) 38 mm (1.5 in) 51 mm (2 in) 76 mm (3 in) 100 mm (4 in)
	2743 mm x 1220 mm (9 ft x 4 ft)	25 mm (1 in) 38 mm (1.5 in) 51 mm (2 in)
Shi lap on 4 edges	2438 mm x 610 mm (8 ft x 2 ft)	25 mm (1 in) 38 mm (1.5 in) 51 mm (2 in) 76 mm (3 in)
Slotted on 2 edges (length)	2438 mm x 610 mm (8 ft x 2 ft)	38 mm (1.5 in) 51 mm (2 in)
Butt on 4 edges	2438 mm x 610 mm (8 ft x 2 ft)	25 mm (1 in) 38 mm (1.5 in) 51 mm (2 in) 76 mm (3 in)
Shi lap dimensions		
Slotted dimensions		
Colour	Light orange	

* Other thicknesses and dimensions available upon request.
(All values are nominal)



SOPREMA.US • 1.800.356.3521

SOPREMA.CA • 1.877.MAMMOUTH

NOTE: All products manufactured by SOPREMA Inc. comply with the description and properties indicated in the technical data sheet that was current at the date of manufacture.

TDS_SOPRA-XPS_20.indd

SOPRA-XPS 20



INSULATION

APPLICATIONS

WALLS

TECHNICAL DATA SHEET 190903SCANE

(supersedes 190805SCANE)

PROPERTIES

SOPRA-XPS 20 meets the requirements of CAN/ULC S701.1 Type 3 (ASTM C578-14 Type X).

Properties	Standards	SOPRA-XPS 20
Thermal Resistance ¹ (RSI-Value [R Value] / 25.4 mm [1 in] @ 24 °C [75 °F])	ASTM C518	RSI- 0.88 (R – 5.0)
Water Vapour Permeance	ASTM E96 (Method A)	57 ng/Pa•s•m ² (1.0 perm)
Flame spread rating	CAN/ULC-S102.2 ²	> 25 < 500
Dimensional Stability, max.	ASTM D2126	1.5 %
Min. Flexural Strength	ASTM C203	500 kPa (73 psi)
Water Absorption, % by volume, max.	ASTM D2842	0.7
Min. Compressive Strength	ASTM D1621	140 kPa (20 psi)
Limiting Oxygen Index	ASTM D2863	24 %

(All values are nominal)

1. The long-term thermal performance (LTTR) of **SOPRA-XPS 20** complies with CAN/ULC S701.1 standard requirement: min. RSI-1.62 (R-9.2) for Type 3 products that are 50 mm (2 in) thick. Please consult your **SOPREMA** representative for more information.

2. CAN/ULC S102.2 : Standard Method of Test for Surface Burning Characteristics of Flooring, Floor Covering, and Miscellaneous Materials and Assemblies

STORAGE AND HANDLING

SOPRA-XPS 20 thermal insulation boards are covered with a temporary waterproof packaging for handling the panels in the manufacturing plant and during transit.

SOPRA-XPS 20 thermal insulation boards must be stored on a flat substrate in their original packaging. If the products are stored outdoors, cover them with an opaque protective cover if the original packaging is removed so that the boards are always protected from UV and sheltered from inclement weather. As they are flammable, they must be protected and kept away from flames and intense heat sources during transportation, handling, storage, and installation.



SOPREMA.US • 1.800.356.3521

SOPREMA.CA • 1.877.MAMMOUTH

NOTE : All products manufactured by SOPREMA Inc. comply with the description and properties indicated in the technical data sheet that was current at the date of manufacture.

TDS_SOPRA-XPS_20.indd