

SENTINEL PVC PIPE FLASHINGS

TECHNICAL DATA SHEET 200923SCANE

(supersedes 200513SCANE)



ACCESSORY PRODUCTS

APPLICATIONS

ROOFS

DESCRIPTION

SENTINEL PVC PIPE FLASHING are prefabricated pieces of membrane composed of thermoplastic polyvinyl chloride (PVC) and a fiberglass reinforcement. They are specially designed to be installed on protrusions up to 152 mm (6 in) in diameter. **SENTINEL PVC PIPE FLASHING** are available in white and grey.

INSTALLATION

The base of the **SENTINEL PVC PIPE FLASHING** is welded to the PVC field surface membrane using an electric hot air welder. The top the the **SENTINEL PVC PIPE FLASHING** is sealed with **SENTINEL UNIVERSAL SEALANT** and a pipe clamp (included).

FOR COMPLETE INFORMATION ON PRODUCT INSTALLATION, PLEASE CONSULT YOUR SOPREMA REPRESENTATIVE.

PACKAGING

Specifications	SENTINEL PVC PIPE FLASHING
Thickness	1.5 mm (60 mil)
Reinforcement	Glass fiber
Diameter	25 to 152 mm (1 to 6 in)
Height	203 mm (8 po)
Underface	Bare-backed
Qty/pal	8

(All values are nominal)

STORAGE AND HANDLING

SENTINEL PVC PIPE FLASHING should be stored in a clean and dry location, away from heat and moisture, on a pallet covered with tarps if needed.



SOPREMA.US • 1.800.356.3521

SOPREMA.CA • 1.877.MAMMOUTH

NOTE: All products manufactured by SOPREMA Inc. comply with the description and properties indicated in the technical data sheet that was current at the date of manufacture.