

SAFETY DATA SHEET

SOPRASEAL LM 203

Offerte en français



SECTION I: IDENTIFICATION

Use: Spray applied vapour-permeable air barrier membrane used in wall construction.

Manufacturer: <u>Distributors</u>:

Soprema CanadaSoprema Inc.Soprema USASoprema USA1675 Haggerty Street44955 Yale Road West310 Quadral Drive12251 Seaway RoadDrummondville (Quebec) J2C 5P7Chilliwack (BC) V2R 4H3Wadsworth (Ohio) 44281Gulfport (Mississippi) 39507

CANADA CANADA UNITED STATES UNITED STATES
Tel.: 819 478-8163 Tel.: 604 793-7100 Tel.: 1 800 356-3521 Tel.: 228 701-1900

In case of emergency:

SOPREMA (8:00am to 5:00pm): 1 800 567-1492 CANUTEC (Canada) (24h.): 613 996-6666 CHEMTREC (USA) (24h.): 1 800 424-9300

SECTION II: HAZARD(S) IDENTIFICATION

DANGER

May cause an allergic skin reaction. Suspected of causing cancer. May cause genetic defects. Causes damage to organs (lungs) through prolonged or repeated exposure (inhalation). May damage fertility or the unborn child. Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not eat, drink or smoke when using this product. Do not breathe vapours. Wash hands thoroughly after handling. Wear protective gloves and eye protection. Get medical attention or call a poison center if you feel unwell or if exposed or concerned. Contaminated work clothing must not be allowed out of the workplace. Store locked up. Avoid release to the environment. Dispose of the container in accordance with local, regional or national regulations.

| SECTION III: COMPOSITION AND INFORMATION ON HAZARDOUS INGREDIENTS | | | | |
|---|------------|----------|------------------------|---------------|
| NAME | CAS# | % WEIGHT | EXPOSURE LIMIT (ACGIH) | |
| | | | TLV-TWA | TLV-STEL |
| Quartz | 14808-60-7 | 25-50 | 0.025 mg/m^3 | Not available |
| Titanium dioxide | 13463-67-7 | 0.3-3 | 10 mg/m^3 | Not available |
| Diuron | 330-54-1 | 0-0.1 | 10 mg/m^3 | Not available |
| 1,2-benzisothiazol-3(2H)-one | 2634-33-5 | 0-0.1 | Not available | Not available |
| 3-iodo-2-propynyl butylcarbamate | 55406-53-6 | 0-0.1 | Not available | Not available |

SECTION IV: FIRST-AID MEASURES

SKIN CONTACT

Wash with plenty of water. If skin irritation occurs: Get medical advice. Take off immediately all contaminated clothing and wash it before reuse.

EYE CONTACT

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice.

INHALATION

Remove person to fresh air and keep comfortable for breathing. Call a poison center if you feel unwell.

SWALLOWING

Immediately call a poison center. Do NOT induce vomiting. Rinse mouth.

SECTION V: FIRE-FIGHTING MEASURES

FLAMMABILITY: Not flammable

EXPLOSION DATA: Sensitivity to mechanical impact: No

Sensitivity to static charge: No

FLASH POINT: Not available

AUTO-IGNITION TEMPERATURE: Not available **FLAMMABILITY LIMITS IN AIR:** Not applicable

FIRE AND EXPLOSION HAZARDS

This product and its vapours are not flammable or combustible.

COMBUSTION PRODUCTS

Irritating and/or toxic gases or fumes may be generated by thermal decomposition or combustion. Toxic and/or irritating gases or fumes can emanate from empty containers when submitted to high temperatures: CO, CO₂.

FIRE FIGHTING INSTRUCTIONS

Evacuate area. Wear self-contained breathing apparatus and appropriate protective clothing in accordance with standards. Approach fire from upwind and fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Always stay away from containers because of the high risk of explosion. Stop leak before attempting to put out the fire. If leak cannot be stopped, and if there is no risk to the surrounding area, let the fire burn itself out. Move containers from fire area if this can be done without risk. Cool containers with flooding quantities of water until well after fire is out.

MEANS OF EXTINCTION

Foam, dry powder, carbon dioxide, water spray, sand. Do not use a heavy water stream.

SECTION VI: ACCIDENTAL RELEASE MEASURES

RELEASE OR SPILL

Ventilate area. Wear appropriate protective equipment during cleanup. Shut off source of leak if it can be done without risk. Contain the spill. Absorb with inert material such as sand or earth. Sweep or shovel into containers with lids. Cover and remove to appropriate well-ventilated area until disposal. Wash spill area with soap and water. Prevent entry into waterways, sewers or basements. Dispose of this product according to local environmental regulations.

Sopraseal LM 203 Revision date: May 6, 2016 Page 1 of 2

SECTION VII: HANDLING AND STORAGE

HANDLING

Avoid contact with eyes, skin and clothing. Do not ingest. Avoid breathing mist, vapour or dust. Wash thoroughly after handling. Before handling, it is very important that ventilation controls are operating and protective equipment requirements are being followed. People working with this product would be properly trained regarding its hazards and its safe use. Contaminated work clothing must not be allowed out of the workplace.

STORAGE

Store away from incompatible materials. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. Have appropriate fire extinguishers and spill clean-up equipment near storage area. Inspect all containers to make sure they are properly labelled.

SECTION VIII: EXPOSURE CONTROLS / PERSONAL PROTECTION

HANDS: Wear nitrile gloves.

RESPIRATORY: If the TLV is exceeded, if use is performed in a poorly ventilated confined area, use an approved respirator in accordance with standards.

EYES: Wear chemical safety goggles or safety glasses in accordance with standards.

OTHERS: Eye bath and safety shower.

CONTROL OF VAPOURS: Local exhaust is needed to control vapour and dust level to below recommended limits

SECTION IX: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid pink **ODOUR AND APPEARANCE:** Not available **ODOUR THRESHOLD: VAPOUR DENSITY (air = 1):** Not available **EVAPORATION RATE (Butyl acetate = 1):** Not available **BOILING POINT (760 mm Hg):** Not available FREEZING POINT: Not available **SPECIFIC GRAVITY (H_2O = 1):** 1.47-1.54 kg/L **SOLUBILITY IN WATER (20°C):** Partial 8-9.5 VOLATILE ORGANIC COMPOUND (V.O.C.) CONTENT: 21 g/L VISCOSITY: Not available

SECTION X: STABILITY AND REACTIVITY

STABILITY: This material is stable.

CONDITIONS OF REACTIVITY: Not available. **INCOMPATIBILITY:** Strong acids, strong bases.

HAZARDOUS DECOMPOSITION PRODUCTS: Fumes, carbon monoxide, carbon dioxide.

CONDITIONS TO AVOID: Avoid excessive heat or cold.

HAZARDOUS POLYMERISATION: None

SECTION XI: TOXICOLOGICAL INFORMATION

TOXICOLOGICAL DATA

Titanium dioxide: (1)

 LC_{50} (rat): 6.8 mg/l (4-hour exposure)

LD₅₀ (oral, rat): > 10 000 mg/kg LD₅₀ (dermal, rabbit): > 10 000 mg/kg

Diuron: (1)

 LD_{50} (oral, rat): 1 017 mg/kg LD_{50} (dermal, rat): > 5 000 mg/kg

1,2-benzisothiazol-3(2H)-one: (1) LD₅₀ (oral, rat): 1 020 mg/kg 3-iodo-2-propynyl butylcarbamate: (1)

LC₅₀ (rat): 0.67 mg/l (4-hour exposure)

LD₅₀ (oral, rat): 300 - 500 mg/kg LD₅₀ (dermal, rat): > 2 000 mg/kg

SECTION XII: ECOLOGICAL INFORMATION

ENVIRONMENTAL EFFECTS

Do not allow product or runoff from fire control to enter grounds, basements, storm or sanitary sewers, lakes, rivers, streams or public waterways. Block off drains and ditches. Provincial and federal regulations may require that environmental and / or agencies be notified of a spill incident. Spill area must be cleaned and restored to original condition or to the satisfaction of authorities. May be harmful to aquatic life.

SECTION XIII: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL

This product is considered as dangerous material. Consult local, state, provincial or territory authorities to know disposal methods. This material is also known as dangerous waste by RCRA (USA); disposal should follow EPA regulations.

SECTION XIV: TRANSPORT INFORMATION

Not regulated

SECTION XV: REGULATORY INFORMATION

DSL: All constituents of this product are included in the Domestic Substances List (DSL – Canada).

TSCA: All constituents of this product are included in the Toxic Substances Control Act Inventory (TSCA – USA).

Prop. 65: This product contains a chemical known to the State of California to cause cancer.

SECTION XVI: OTHER INFORMATION

GLOSSARY

ASTM: American Society for Testing and Materials (United

States)

CAS: Chemical Abstract Services

CSA: Canadian Standardization Association
DOT: Department of Transportation (United States)
EPA: Environmental Protection Agency (United States)

GHS Globally Harmonized System

LD₅₀/**LC**₅₀: Less high lethal dose and lethal concentration published **NIOSH:** National Institute for Occupational Safety and Health

(United States)

RCRA: Resource Conservation and Recovery Act (United

States)

TDG: Transportation of Dangerous Goods (Canada)
TLV-TWA: Threshold Limit Value – Time-Weighted Average

Reference:

(1) Manufacturer's SDS

Code of SDS: CA U DRU SS FS 209

For more information: 1 800 567-1492

The Safety Data Sheets of SOPREMA Canada are available on Internet at the following site: www.soprema.ca

Justification of the update:

• New product.

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.