



ACCESSORY PRODUCTS

APPLICATIONS

WALLS

INDOOR APPLICATIONS

SOPRA-CELLULOSE PATCH

TECHNICAL DATA SHEET 180222SCANE

(supersedes 171204SCANE)

DESCRIPTION

SOPRA-CELLULOSE PATCH is a self-adhesive patch used to close the injection holes in the restraint membrane after SOPRA-CELLULOSE cellulosic fibre insulation has been applied in walls, roofs and ceilings.

INSTALLATION

Install SOPRA-CELLULOSE PATCH over the openings in the restraint membrane, making sure that the membrane is free of any moisture or dust. The patch must adhere perfectly in order to guarantee the integrity of the vapour barrier system.

Service temperature : > -5°C (> 23°F)

NOTE: At low temperatures, use web spray adhesive.

FOR COMPLETE INFORMATION ON PRODUCT INSTALLATION, PLEASE CONSULT YOUR REPRESENTATIVE.

PACKAGING

Specifications	SOPRA-CELLULOSE PATCH
Dimension	152.4 mm (6 in) diameter
Qty/package	100 units/roll
Weight	0.5 kg/roll (1.1 lb/roll)

PROPERTIES

Properties	Standards	SOPRA-CELLULOSE PATCH
Water vapour transmission	ASTM E96 (Method A)	0.1 ng/Pa•s•m ² (0.002 Perm)
Adhesive strength @ -5°C	ASTM D1876	400 N/m (2.30 lbf/in)
Adhesive strength @ 22°C	ASTM D1876	460 N/m (2.70 lbf/in)

(All values are nominal)

STORAGE AND HANDLING

Store SOPRA-CELLULOSE PATCH in a cool, dry place and protect from moisture, direct sunlight and weather during shipping, handling, storage and installation.



SOPREMA.US • 1.800.356.3521

SOPREMA.CA • 1.877.MAMMOUTH

TDS_SOPRA_CELLULOSE_PATCH.indd