


SOPRA-ISO TRANSITION PANEL

ROOFS



INSULATION



SLOPE INSULATION

The first polyisocyanurate panel in the industry with a thickness of almost 0 inch at the lowest point. These transition panels – available in 2% and 4% – provide a smooth transition at crickets and back slopes unlike traditional panels that require excessive thinning and shaving on site. As they are economical, they help reduce the amount of insulation and associated costs. They can be used as starter panels, crickets, back slopes and perimeter slopes.

- Promotes positive drainage
- Harmonizes the transition of panels by eliminating the unevenness at the edges of crickets and back slopes

PROPERTIES	
Surface	Organic facers reinforced with glass fibres
Underface	Organic facers reinforced with glass fibres
Technology	Polyisocyanurate
Application	Adhesive Adhered with hot bitumen Mechanically fastened
Length	1.22 m (4 ft)
Width	1.22 m (4 ft)
Service Temperature	-73 to 122 °C (-100 to 250 °F)

PRODUCT	CODE	BOARD DESCRIPTION	SLOPE	THICKNESS (MIN.)	THICKNESS (MAX.)	UNITS PER SKID
SOPRA-ISO TRANSITION PANEL	41358	GG	2%	0 mm (0 in)	25.4 mm (1 in)	76
	41339	P	4%	0 mm (0 in)	50.8 mm (2 in)	42

Data and information are subject to change without notice. Please refer to our website.



TIP: This product comes in several varieties. We suggest calling your sales representative for more information on this product and to place an order.