

SOPRAMASTIC

TECHNICAL DATA SHEET ANZ-TDS-43-SOPRAMASTIC

DESCRIPTION

SOPRAMASTIC is a black, solvent-based mastic containing SBS modified bitumen, fibres and mineral fillers. It is an ideal complement for bituminous waterproofing membranes and is used as jointing mastic, caulking material and joint filler. It is compatible with bituminous materials and ensures good waterproofing.

SOPRAMASTIC is a multi-purpose mastic that has been formulated with a high level of polymer in order to resist flow at high temperatures. Furthermore, it is easy to manipulate at temperatures down to -10 °C.

APPLICATION

SOPRAMASTIC must be applied to clean, sound substrates.

SOPRAMASTIC tubes can be used with a standard cartridge extruder.

Excellent adherence on most materials without primer. It can be applied to damp surfaces.

SHOULD NOT BE USED AS A PITCH POCKET FILLER.

FOR COMPLETE INFORMATION ON PRODUCT INSTALLATION, PLEASE CONSULT YOUR SOPREMA REPRESENTATIVE.

PROPERTIES

SOPRAMASTIC meets the requirements of CAN/CGSB-37.5-M89 and ASTM D4586 standards.

Properties	Standards	SOPRAMASTIC
Specific Gravity at 20 °C	-	1.12 kg/L
Colour	-	Black
Application temperatures Range	-	-10 to 35°C
Service temperatures Range	-	-40 to 80°C
Solids by Weight	-	83 %
Setting time	-	Between 4 and 24 hours, depending on temperature and quantity applied.

(All values are nominal)

PACKAGING

310 ml (20 per boxes) & 800 ml cartridges, and 10 L pails.

STORAGE & HANDLING

Shelf life: Up to 36 months in original sealed containers.

Tools can be cleaned with petroleum solvents such as mineral spirits, varsol, xylene, etc.

SOPRAMASTIC is a **flammable** product. Store in a cool, dry area.

CONSULT THE MATERIAL SAFETY DATA SHEET PRIOR TO USE.



SOPRAMASTIC

TECHNICAL DATA SHEET ANZ-TDS-43-SOPRAMASTIC

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this publication is based on the present state of our best knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by Commonwealth or State Legislation. The owner, their representative or the contractor is responsible for checking the suitability of products for their intended use.

Note: Field service where provided, does not constitute supervisory responsibility. Suggestions made by Soprema Australia Pty Ltd either verbally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not Soprema Australia Pty Ltd are responsible for carrying out procedures appropriate to a specific application.

DOCUMENT CONTROL	
Product	SOPRAMASTIC
Initial Issue	30.10.2019
Amendment	
Author	JJ

