





**APPLICATIONS** 

ROOFING BALCONIES

# ALSAN 076

TECHNICAL DATA SHEET

APTDS-F-172-01

## **DESCRIPTION**

ALSAN 076 is a solvent-based cleaning agent for the Alsan PMMA range.

## **PROPERTIES**

	ALSAN 076
Colour	colourless
Relative density (20 °C) (kg/m3)	902
Composition	ethyl acetate based
Flash point (°C)	-4
Flammability	highly flammable

## **APPLICATION**

ALSAN 076 is used for cleaning tools. It can also be used for cleaning of substrates.

### **PACKAGING AND STORAGE**

Can of 1, 10 or 30 litre.

Store in original sealed packaging in a cool, dry and frost-free place at a temperature between 5 and 35 °C. Do not expose to direct sunlight and lower temperatures. Unopened products have a shelf life of at least 5 years. After opening, reseal the packaging so it is completely airtight.

## **APPLICATION**

## Cleaning tools

Uncured Alsan PMMA resin can be washed out/wiped off.

Before reusing the tools the solvent needs to be evaporated completely.

#### Cleaning substrates

**ALSAN 076** is used for the cleaning of TPO and PVC membranes of the Flag range and substrates equipped with an Alsan PMMA system. Furthermore, it is used to clean substrates such as glass (without coating), metal, and synthetics such as polyester, and PVC. It is recommended to perform a test in advance.













**APPLICATIONS** 

ROOFING BALCONIES

## ALSAN 076

TECHNICAL DATA SHEET

APTDS-F-172-01

## SPECIAL INDICATIONS

Please refer to the safety data sheet for the relevant product.

#### Hygiene, health and Environment

ALSAN 076 contains solvents.

For more information, please refer to the relevant safety data sheet.



#### **Quality and Environment Management**

SOPREMA has always attached the highest importance to the quality of the products and the environment.

For this reason, we operate independently monitored Quality and Environment Assurance Systems in line with EN ISO 9001 and EN ISO 14001.

## **GENERAL INFORMATION**

The above information, in particular the product application information, is based on extensive development and many years of experience. It is provided to the best of our knowledge. However, the wide range of requirements and conditions on site means that it may be necessary for the product to be tested under those conditions to ensure that it is suitable for the intended purpose. For further information and questions, contact **SOPREMA**.

Only the most recent version of the document is valid. We reserve the right to make changes to reflect advances in technology and improvements to our products.





