SOPRASEAL STICK VP by Soprema

Health Product Declaration v2.2

created via: HPDC Online Builder

HPD UNIQUE IDENTIFIER: 20782 CLASSIFICATION: 07 27 00

PRODUCT DESCRIPTION: SOPRASEAL STICK VP is a self-adhesive, sheet-applied, vapour permeable air barrier and weather-resistive barrier for exterior walls. This product can be used on most substrates, such as masonry, concrete, wood and gypsum. The air barrier assembly comprising SOPRASEAL STICK VP obtained the A1 classification when tested under CAN/ULC-S742.

	_	
	Ħ	
	Ħ	
	۰	

Section 1: Summary

Nested Method / Material Threshold

	JTF			

Inventory Reporting Format	Threshold level	Residuals/Impurities	All Substances Abov	ve the Threshold Indicated Are:
Nested Materials Method Basic Method	● 100 ppm● 1,000 ppm	Residuals/Impurities Considered in 0 of 3 Materials	Characterized % weight and role p	C Yes Ex/SC • Yes C No
Threshold Disclosed Per	for Residuals/Impurities?	Screened	C Yes Ex/SC ⊙ Yes C No	
Material Product		• Yes • No	All substances scree results disclosed.	ened using Priority Hazard Lists with

Identified O Yes Ex/SC O Yes O No One or more substances not disclosed by Name (Specific or Generic) and Identifier and/ or one or more Special Condition did not follow guidance.

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

MATERIAL | SUBSTANCE | RESIDUAL OR IMPURITY

GREENSCREEN SCORE | HAZARD TYPE

POLYPROPYLENE BARRIER [POLYPROPYLENE LT-UNK] ACRYLIC ADHESIVE [UNDISCLOSED NoGS] SILICONIZED PET FILM [

POLYETHYLENE TEREPHTHALATE (PET) LT-UNK

POLYDIMETHYLSILOXANE RUBBER (POLYSILICONE-11) NoGS]

Number of Greenscreen BM-4/BM3 contents ... 0

Contents highest concern GreenScreen Benchmark or List translator Score ... LT-UNK

Nanomaterial No.

INVENTORY AND SCREENING NOTES:

No substance other than those listed in this HPD have been added to the finished product during its manufacturing. Residuals or impurities could not be considered because information was not provided to the manufacturer by the raw materials vendors. Ranges were given for various substances to protect proprietary information; .

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

VOC Content data is not applicable for this product category.

CERTIFICATIONS AND COMPLIANCE See Section 3 for additional listings.

VOC emissions: CDPH Stantard Method - N/A

CONSISTENCY WITH OTHER PROGRAMS

Pre-checked for LEED v4 Material Ingredients, Option 1 and Option 2

Third Party Verified?

C Yes No

PREPARER: Self-Prepared

VERIFIER: VERIFICATION #: SCREENING DATE: 2020-06-23 PUBLISHED DATE: 2020-06-23 EXPIRY DATE: 2023-06-23



Section 2: Content in Descending Order of Quantity

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.1.1, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-1-1-standard

POLYPROPYLENE BARRIER %: 47.0000 - 49.0000

MATERIAL THRESHOLD: 100 ppm

RESIDUALS AND IMPURITIES CONSIDERED: No

MATERIAL TYPE: Polymeric Material

RESIDUALS AND IMPURITIES NOTES: Redisuals and impurities could not be considered as information was not available from raw material vendors.

OTHER MATERIAL NOTES: Top component of the product, responsible for its air barrier and water resistive performance, as well as its water vapour diffusion.

POLYPROPYLENE ID: 9003-07-0 HAZARD SCREENING METHOD: Pharos Chemical and Materials Library HAZARD SCREENING DATE: 2020-06-23 %: 100,0000 - 100,0000 GS: LT-UNK SUBSTANCE ROLE: Sealant RC: None NANO: No HAZARD TYPE AGENCY AND LIST TITLES WARNINGS No warnings found on HPD Priority Hazard Lists None found

SUBSTANCE NOTES: A vapour-permeable polypropylene membrane layer is encapsulated between two layers of non-woven polypropylene fabric.

ACRYLIC ADHESIVE %: 40.0000 - 44.0000

MATERIAL THRESHOLD: 100 ppm

RESIDUALS AND IMPURITIES CONSIDERED: NO

MATERIAL TYPE: Polymeric Material

RESIDUALS AND IMPURITIES NOTES: Redisuals and impurities could not be considered as information was not available from raw material vendors

other material notes: Central portion of the product, responsible for adhesion to various substrates.

UNDISCLOSED

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREE	HAZARD SCREENING DATE: 2020-06-23			
%: 99.0000 - 100.0000	gs: NoGS	RC: None	nano: No	SUBSTANCE ROLE: Adhesive		
HAZARD TYPE AGENCY AND LIST TITLES None found		WARNINGS				
			No warnir	ngs found on HPD Priority Hazard Lists		

SUBSTANCE NOTES: Vapour-permeable acrylic-based adhesive enables adhesion to various substrates while allowing water vapour diffusion. Exact composition of the acrylic polymer is not disclosed to protect proprietary information.

SILICONIZED PET FILM

%: 9.0000 - 11.0000

MATERIAL THRESHOLD: 100 ppm

RESIDUALS AND IMPURITIES CONSIDERED: No

MATERIAL TYPE: Polymeric Material

RESIDUALS AND IMPURITIES NOTES: Redisuals and impurities could not be considered as information was not available from raw material vendors.

OTHER MATERIAL NOTES: Plastic film used on the back side of the product to protect adhesive. To be removed upon application, exposing adhesive and allowing SOPRASEAL STICK VP to be adhered onto a substrate.

POLYETHYLENE TEREPHTHALATE (PET)

ID: 25038-59-9

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2020-06-23			
%: 97.0000 - 99.0000	GS: LT-UNK	RC: None	NANO: No	SUBSTANCE ROLE: Anti-adhesive agent	
HAZARD TYPE	AGENCY AND LIST TITLES		WARNINGS		
None found No warnings found on HPD Priority Hazard Lis					

SUBSTANCE NOTES: The siliconized release film applied to the back of the product is composed primarily of PET polymer.

POLYDIMETHYLSILOXANE RUBBER (POLYSILICONE-11)

ID: 63394-02-5

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2020-06-23			
%: 1.0000 - 3.0000	GS: NoGS	RC: None	nano: No	SUBSTANCE ROLE: Anti-adhesive agent	
HAZARD TYPE	AGENCY AND LIST TITLES		WARNINGS		
None found			No	o warnings found on HPD Priority Hazard Lists	

SUBSTANCE NOTES: Substance responsible of the release property of the release film used on the back of the product.



Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS

CDPH Stantard Method - N/A

CERTIFYING PARTY: Self-declared

ISSUE DATE: 2020-

EXPIRY DATE:

CERTIFIER OR LAB: N/A

APPLICABLE FACILITIES: N/A

06-23

CERTIFICATE URL:

CERTIFICATION AND COMPLIANCE NOTES: N/A - This product is an exterior product therefore is not to be tested for VOC emissions.



Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

SOPRASEAL VP PRIMER

HPD URL: No HPD available

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES:

The use of a primer may be required before the installation of SOPRASEAL STICK VP. In such cases, vapour-permeable SOPRASEAL VP PRIMER (27 g/L VOC content) must be used to maintain the full vapour diffusion potential of SOPRASEAL STICK VP.



Section 5: General Notes

Performance certification: Classification A1 under CAN/ULC-S742 Third-party report dated 2015-08-29 by Exova Maximum air leakage of assembly = 0.0150 L / s m2 at 75 Pa

MANUFACTURER INFORMATION

MANUFACTURER: Soprema

ADDRESS: 1688 Jean-Berchmans-Michaud St.

Drummondville QC J2C8E9, Canada

WEBSITE: www.soprema.ca

CONTACT NAME: Jean-François Côté

TITLE: Director, Standards and Scientific Affairs

PHONE: **819-478-8166 x.3290**EMAIL: **jfcote@soprema.ca**

The listed contact is responsible for the validity of this HPD and attests that it is accurate and complete to the best of his or her knowledge.

KEY

Hazard Types

AQU Aquatic toxicity

CAN Cancer

DEV Developmental toxicity

END Endocrine activity

EYE Eye irritation/corrosivity

GEN Gene mutation

GLO Global warming

LAN Land toxicity

MAM Mammalian/systemic/organ toxicity

MUL Multiple

NEU Neurotoxicity

NF Not found on Priority Hazard Lists

OZO Ozone depletion

PBT Persistent, bioaccumulative, and toxic

PHY Physical hazard (flammable or

reactive)

REP Reproductive

RES Respiratory sensitization

SKI Skin sensitization/irritation/corrosivity

UNK Unknown

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)

BM-3 Benchmark 3 (use but still opportunity for improvement)

BM-2 Benchmark 2 (use but search for safer substitutes)

BM-1 Benchmark 1 (avoid - chemical of high concern)

BM-U Benchmark Unspecified (due to insufficient data)

LT-P1 List Translator Possible 1 (Possible Benchmark-1)

LT-1 List Translator 1 (Likely Benchmark-1)

LT-UNK List Translator Benchmark Unknown (the chemical is present on at least one GreenScreen Specified List, but the information contained within the list did not result in a clear mapping to a LT-1 or LTP1 score.)

NoGS No GreenScreen.

Recycled Types

PreC Pre-consumer recycled content

PostC Post-consumer recycled content

UNK Inclusion of recycled content is unknown

None Does not include recycled content

Other Terms:

GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material Nested Method / Product Threshold Substances listed within each material per threshold indicated per product Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology

Third Party Verified Verification by independent certifier approved by HPDC

Preparer Third party preparer, if not self-prepared by manufacturer

Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- a method for the assessment of exposure or risk associated with product handling or use,
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.