SENTINEL
MOLDED CORNERS

TECHNICAL DATA SHEET 190617SCANE (supersedes -)

ACCESSORY PRODUCTS

APPLICATIONS

ROOFS

DESCRIPTION
The **SENTINEL MOLDED CORNERS** are injection molded membrane pieces, composed of unreinforced thermoplastic polyvinyl chloride (PVC). They are used as reinforcement for 90° inside and outside corners. The **SENTINEL MOLDED CORNERS** are available in white.

INSTALLATION
The **SENTINEL MOLDED CORNERS** are welded to the inside and outside corners of the roof using an electric hot air welder.

FOR COMPLETE INFORMATION ON PRODUCT INSTALLATION, PLEASE CONSULT YOUR SOPREMA REPRESENTATIVE.

PACKAGING

Specifications	SENTINEL MOLDED CORNERS
Thickness	2.2 mm (85 mils)
Dimensions	127 × 127 × 127 mm (5 × 5 × 5 in)
Underface	Bare-backed
Qty/box	20

(All values are nominal)

STORAGE AND HANDLING
SENTINEL MOLDED CORNERS should be stored in a clean and dry location, away from heat and moisture, on a pallet and covered with tarps if needed.

TDS_SENTINEL_MOLDED_CORNERS.indd

SYSTÈME QUALITÉ ISO 9001 QUALITY SYSTEM

SYSTÈME ENVIRONNEMENT ISO 14001 ENVIRONMENT SYSTEM

SOPREMA®

NOTE: All products manufactured by SOPREMA, Inc. comply with the description and properties indicated in the technical data sheet that was current at the date of manufacture.