

# SENTINEL PVC PROFILE BAR

TECHNICAL DATA SHEET 201019SCANE

(supersedes -)



ACCESSORY PRODUCTS

APPLICATIONS

ROOFS

## DESCRIPTION

SENTINEL PVC PROFILE BARS are extruded, pliable PVC bars designed to provide PVC membrane with the appearance of a standing seam metal roof. They are available in white and grey.

## INSTALLATION

Installation of the SENTINEL PVC PROFILE BAR is done by hot air welding. Each profile has a weld base of 34 mm (1.35 in) to attach the bar to the membrane. The profile bar can be installed on both flat and curved surfaces, and can be applied on any slope. When installing the profile bar, tack weld the bar in place to ensure it is straight prior to heat welding the bar in place.

FOR COMPLETE INFORMATION ON PRODUCT INSTALLATION, PLEASE CONSULT YOUR SOPREMA REPRESENTATIVE.

## PACKAGING

Specifications	SENTINEL PVC PROFILE BAR
Colors	White and grey
Width	3.5 mm (1.38 in)
Height	30 mm (1.2 in)
Length	3.0 m (10 ft)
Qty/pal	10

(All values are nominal)

## STORAGE AND HANDLING

All materials must be stored in a clean, dry location and cover as necessary to protect from environmental damage such as extreme cold, heat or moisture. Monitor varying environmental conditions during storage, handling and applications.



SOPREMA.US • 1.800.356.3521

SOPREMA.CA • 1.877.MAMMOUTH

NOTE: All products manufactured by SOPREMA Inc. comply with the description and properties indicated in the technical data sheet that was current at the date of manufacture.