



ACCESSORY
PRODUCTS

APPLICATIONS

ROOFS

FLAGON

LIQUID PVC

TECHNICAL DATA SHEET

ANZ-TDS-80-FLAGON LIQUID PVC

DESCRIPTION

FLAGON LIQUID PVC is used for the cold sealing of the welding on Flagon PVC membranes.

FLAGON LIQUID PVC is compatible with FLAGON PVC membranes.

APPLICATION

FLAGON LIQUID PVC is applied with an applicator on top of the welding.

FOR COMPLETE INFORMATION ON PRODUCT INSTALLATION, PLEASE CONSULT YOUR SOPREMA REPRESENTATIVE.

PACKAGING

SPECIFICATIONS	FLAGON LIQUID PVC
Colour	different colours
Physical aspect	viscous liquid
Weight	1 kg
Consumption	10 g/m
Density at 20°C	0.98 g/cm ³
Ignition temperature (DIN 51755)	-21 °C

VISUAL



STORAGE AND HANDLING

The shelf life is almost 6 months, if the container is hermetically sealed and maintained at a room temperature.

Avoid contact with polystyrene. Do not apply on wet waterproofing membranes.

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this publication is based on the present state of our best knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by Commonwealth or State Legislation. The owner, their representative or the contractor is responsible for checking the suitability of products for their intended use.



SOPREMA.COM.AU • +61 (3) 9221 6230

TDS_FLAGON_LIQUID_PVC_2021_RA

1/1