

SOPRAMASTIC

ALU



ACCESSORY
PRODUCTS

APPLICATIONS

ROOFS

FOUNDATIONS

WALLS

TECHNICAL DATA SHEET

ANZ-TDS-43-SOPRAMASTIC

DESCRIPTION

SOPRAMASTIC ALU is a solvent-based mastic containing SBS synthetic rubber and bitumen. It complements bituminous waterproofing membranes and is used as jointing mastic, caulking material and joint filler. It is compatible with bituminous materials and ensures good waterproofing. It contains leafing aluminium pigmentation providing superior protection against ultraviolet light and its high level of polymer ensures long-term flexibility and elasticity.

INSTALLATION PROCEDURE

SUBSTRATE:

SOPRAMASTIC ALU have an excellent adhesion on a wide variety of surfaces without a primer. Can be applied on damp surfaces.

APPLICATION:

- SOPRAMASTIC ALU must be applied to clean, sound substrates.
- SOPRAMASTIC ALU 310 ml cartridges can be used with a standard cartridge extruder.
- To optimise its reflective properties, avoid contact of water until SOPRAMASTIC ALU is dry.

FOR COMPLETE INFORMATION ON PRODUCT INSTALLATION, PLEASE CONSULT YOUR SOPREMA REPRESENTATIVE.

PACKAGING

SPECIFICATIONS	SOPRAMASTIC ALU
Physical state	Viscous
Colour	Aluminium
Container	0.310 L / 0.800 L
Units per Pallet	1200 / 576

PROPERTIES

PROPERTIES	SOPRAMASTIC ALU
Specific Gravity at 20°C	1.22 kg/L
Application temperatures	-10 to 35°C
Service temperatures	-40 to 80°C
Solids by Weight	85%
Setting time	Between 4 and 24 hours, depending on temperature and quantity applied

STORAGE AND HANDLING

Shelf life: Up to 36 months in original sealed containers in cool and ventilated area. Tools can be cleaned with petroleum solvents such as mineral spirits, varsol, xylene, etc. SOPRAMASTIC ALU is a flammable product. Store in a cool, dry area.

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this publication is based on the present state of our best knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by Commonwealth or State Legislation. The owner, their representative and/or the contractor is responsible for checking the suitability of products for their intended use.



SOPREMA.COM.AU • +61 (3) 9221 6230

TDS_SOPRAMASTIC_ALU_06-2021_RA

1/1