

## **RESISTOSOUND SOUNDPROOFING PRODUCT LINE**

fig.1





## **INSTALLATION GUIDE**

- Slide the product vertically behind the pipe to be soundproofed by pressing on the jointing or on a previously installed section of ACOUSTIDRAIN to ensure the product is straight and to facilitate closure of the joint (fig. 1).
- Next, remove the pre-cut section of the silicone film to the opposite side of the overlapping joint of the ACOUSTIDRAIN product (fig. 2 and 3).
- 3 After removing the silicone film, stick that section onto the pipe (fig. 4).
- 4 The opposite side (the overlapping joint) is treated the same way, by cutting the silicone film as closely as possible to the pipe (fig. 5).



fig.5

fig.3





fig.4



PEACE OF MIND RELAXING COMFORT PEACEFUL HOME



A solution from



## **ACOUSTIDRAIN**

SOUNDPROOFING PRODUCT FOR DRAINPIPE

## **INSTALLATION GUIDE (CONTINUE)**

- 5 Close off the overlapping joint by first removing the silicone film from the overlapping section (fig. 6) then closing the previously affixed self-adhesive joint of the ACOUSTIDRAIN product (fig. 7).
- The overlapping joint is then kept sealed using the tie-wraps provided in the kit. Place one at each end, as well as one at the centre, about 49.5 cm (19½ in.) from the ends. Close the joints between the sections with duct tape (fig. 8).
- 7 Next treat the elbows using 32 cm x 49.5 cm (12¾ in. x 19½ in.) pieces of foam with the black film supplied in the kit. The 32-cm section should be placed perpendicular to the elbows and then wrapped around the elbows in such a way as to overlap.

It is secured using tie-wraps supplied in the kit; there should be one in the centre and one at each end. Take care to place the black film on the outside.

The foam piece must also overlap the previously installed ACOUSTIDRAIN product (fig. 9).

For a more aesthetically pleasing installation, the excess pieces of foam can be trimmed at right angles so they don't stick out (fig. 10).




fig.6

fig.7



fig.10



fig.9



fig.8



1640 Haggerty, Drummondville (Québec) J2C 5P8

Phone: **819 478.8408** | Fax: **819 478.0199** 

**CUSTOMER SERVICE: 1 877 478.8408** 

www.resisto.ca

