


SELECT MOD G2 BASE

BASE SHEET MEMBRANE



Base sheet membrane consisting of SBS modified bitumen applied onto a glass mat reinforcement, sanded on both sides.

- Excellent resistance to temperature variations
- Excellent dimensional stability

PRODUCT PURPOSE

Application	Sealing	
Building Part	Roofing	
Types of Slope	Very low slope	Negative slope with internal drain
Type of Coating	Bitumen membrane	

PRODUCT CHARACTERISTICS

Technology	SBS polymer modified bitumen
Surface	Sand
Underface	Sand
Reinforcement	Glass mat
Installation Method	Glued with hot bitumen

PACKAGING

Code	Width		Length		Thickness		Net Area		Units (per pallet)
	in	m	ft	m	mils	mm	ft ²	m ²	
8 86442 08106 7	36	1	98.23	29.94	47	1.2	295	29.94	20

INSTALLATION

Storage	Rolls should be stored upright, tape side up. If the products are stored outdoors, cover them with an opaque protective cover after removing the delivery packaging. Can withstand frost, but must be reactivated for 24 hours to at least 10 °C (50 °F) prior to installation.
Minimum Application Temperature	40 °F (4.5 °C)
Surface Preparation	The substrate must be clean, dry and free of dust, grease or other contaminants.
Recommendations/ Limitations	It is not recommended to install the membrane directly on wood boards. Cover the surface with a suitable panel or an underlayment membrane prior to the installation of the membrane. It is not recommended to use a product containing bitumen directly on softwood boards or flexible polyvinyl chloride.

