

OIL SPOT PRIMER

FOR ASPHALT SURFACES



The OIL SPOT PRIMER is a polymer emulsion that enhances the adhesive strength of asphalt driveway sealers on asphalt surfaces affected by oil spills.

- Optimizes adhesive strength of asphalt driveway sealers

PRODUCT PURPOSE

Application	Asphalt surface protection
Substrate	Asphalt

PRODUCT CHARACTERISTICS

Installation Method	Paint brush applied
---------------------	---------------------

PACKAGING

Code	Containers	Units per box	Boxes per skid
50004	946 ml (0.25 gal)	12	40

INSTALLATION

Storage	3 years in the original container. Store in a cool, dry place, between 10 ° C (50 ° F) and 40 ° C (104 ° F). Keep from freezing.
Minimum Application Temperature	10 ° C (50 ° F)
Surface Preparation	Sweep away all dirt and debris from the surface.
Installation Prerequisite	First, treat the oil spot with RESISTO CLEANER AND DEGREASER (follow the instructions supplied with the product).
Installation	1. After cleaning the surface, shake vigorously and apply a thin coat of OIL SPOT PRIMER using a brush. 2. Let dry completely.
Drying time	Let dry for at least 24 hours under ideal conditions. Drying time may vary depending on ambient temperature, humidity level and the amount applied.
Cleaning	Clean damp tools with water. When dry, clean with solvents such as mineral spirits, paint thinner or xylene.
Tricks / Tips	Allow product to cure completely before applying a driveway sealer. To ensure long-lasting protection of the asphalt surface, seal it using a RESISTO driveway sealer. If the asphalt surface is softened by oil or gasoline, it is suggested to remove the damaged area and to repair it with RESISTO ASPHALT REPAIR.
Recommendations/ Limitations	Avoid applying the product if there is a risk of rain, high humidity or frost within 24 hours of application. Apply on asphalted pavements that are least 6 months old. Apply without dilution or thinning. Do not apply solvent-based sealant on this product.