

RUBBERIZED CRACK FILLER

FOR ASPHALT SURFACES



The rubberized crack filler for asphalt surfaces is designed to repair cracks, joints, and other damage to asphalted surfaces. It prevents damage to asphalt surfaces caused by wear, rain and frost.

- **Strongly adheres to the walls of cracks**
- **Remains flexible**
- **Highly resistant to temperature variations**

PRODUCT PURPOSE

Application	Asphalt surface protection
Substrate	Asphalt

PRODUCT CHARACTERISTICS

Installation Method	Caulk gun applied
---------------------	-------------------

PACKAGING

Code	Containers	Coverage	Units per box	Boxes per skid
50003	300 ml (10 oz)	6 m (19 lin. ft.)	20	60

INSTALLATION

Storage	2 years in the original container. Store in a cool, dry place. Can support storage temperatures below 0 °C (32 °F).
Minimum Application Temperature	10 °C (50 °F)
Surface Preparation	Clean the cavities using water, let dry completely. The substrate must be clean and dry.
Installation Prerequisite	Designed for cracks up to 10 mm (3/8 in) in width and depth.
Installation	<ol style="list-style-type: none"> 1. Cut the spout at a 90° angle, so the opening is 10 mm (3/8 in) wide. 2. Fill deep cracks using sand up to 3/8 in. (10 mm) of the top surface. 3. Break the seal inside the spout. 4. Apply RESISTO RUBBERIZED CRACK FILLER directly onto cracks and let dry.
Drying time	Let dry for at least 24 hours under ideal conditions. Drying time may vary depending on ambient temperature, humidity level and the amount applied.
Cleaning	Clean damp tools with water. When dry, clean with solvents such as mineral spirits, paint thinner or xylene.
Tricks / Tips	For largers cracks and other repairs, use LEVELLING PATCH or ASPHALT REPAIR. Allow product to cure completely before applying a driveway sealer. To ensure long-lasting protection of the asphalt surface, seal it using a RESISTO DRIVEWAY SEALER.
Recommendations/ Limitations	Avoid applying the product if there is a risk of rain, high humidity or frost within 24 hours of application. Apply without dilution or thinning.