

## LIQUID CRACK FILLER

### FOR ASPHALT SURFACES



The RESISTO liquid crack filler for asphalt surfaces is designed to repair small cracks and joints into asphalt pavement. The RESISTO liquid crack filler protects against water infiltration into asphalt pavement breakdown caused from wear, rain and freezing temperatures.

- Fills small cracks
- Ready to use in a squeeze container
- Flexible asphalt and rubber-based coating

#### PRODUCT PURPOSE

Application	Asphalt surface protection
Substrate	Asphalt

#### PRODUCT CHARACTERISTICS

Installation Method	Squeeze container
---------------------	-------------------

#### PACKAGING

Code	Containers	Units per box	Boxes per skid
50012	946 ml (0.25 gal)	12	40
50006	3.78 L (1 gal)	6	21

#### INSTALLATION

Storage	2 years in the original container. Store in a cool, dry place, between 10 ° C (50 ° F) and 40 ° C (104 ° F). Keep from freezing.
Minimum Application Temperature	10 ° C (50 ° F)
Surface Preparation	The substrate must be dry and free of dust, grease or other contaminants.
Installation Prerequisite	Designed for cracks up to 1/4 in (6 mm) wide.
Installation	<ol style="list-style-type: none"> <li>1. Shake vigorously and cut the spout at a 45° angle.</li> <li>2. Apply RESISTO LIQUID CRACK FILLER directly onto cracks and let dry.</li> <li>3. Repeat application if needed.</li> </ol>
Drying time	Let dry for at least 24 hours under ideal conditions. Drying time may vary depending on ambient temperature, humidity level and the amount applied.
Cleaning	Clean damp tools with water. When dry, clean with solvents such as mineral spirits, paint thinner or xylene.
Tricks / Tips	For largers cracks and other repairs, use RUBBERIZED CRACK FILLER, LEVELLING PATCH or ASPHALT REPAIR. Allow product to cure completely before applying a driveway sealer. To ensure long-lasting protection of the asphalt surface, seal it using a RESISTO driveway sealer.
Recommendations/ Limitations	Avoid applying the product if there is a risk of rain, high humidity or frost within 24 hours of application. Apply without dilution or thinning.