

ASPHALT RESTORER 6 YEARS



PROTECTION

Water-based, acrylic coating (coal tar-free) used to prevent cracks and deterioration caused by wear, freezing, oil and gas spills, salt sand and rain.

- Has a very black and shiny finish
- No unpleasant odor
- Easy and fast application

PRODUCT PURPOSE

Application	Asphalt surface protection
Substrate	Asphalt


PRODUCT CHARACTERISTICS

Installation Method	Roller
---------------------	--------

PACKAGING

Code	Containers	Indicative Covering	Quantity per Pallet
50049	17 l (4.5 gal US)	32 to 75 m ² (350 to 800 ft ²)	36

INSTALLATION

Storage	3 years in the original container. Store in a cool, dry place, between 10 ° C (50 ° F) and 40 ° C (104 ° F). Keep away from frost.
Min. Application Temperature	10 ° C (50 ° F)
Tools Required	 Roller
Surface Preparation	The substrate must be clean, dry and free of dust, grease or other contaminants.
Installation Prerequisite	Before hand repair the surface with RESISTO asphalt maintenance range of products.
Installation	<ol style="list-style-type: none"> 1. To clean the surface, spray water, then using a brush remove any vegetation, dirt or dust. 2. Mix thoroughly until smooth. To facilitate the mixing of the coating, we recommend using a drill equipped with a mixer attachment. 3. Start by the highest part of the surface to be covered. 4. Pour the ACRYLIC ASPHALT RESTORER in ribbon shapes and apply the product with a roller, taking care not to leave any excess product on the surface.
Drying time	24 hours
Cleaning	Clean damp tools with water. When dry, clean with solvents such as mineral spirits, paint thinner or xylene.
Tricks / Tips	For best results, do not apply the product in direct sunlight.
Recommendations/ Limitations	Avoid applying the product if there is a risk of rain, high humidity or frost within 24 hours of application. The asphalt repair must cure for a minimum of 15 days before the application of the ASPHALT RESTORER. Do not apply on surface if a coal-tar coating has been applied and is still in good condition.

