



SOPREMA FOR MANUFACTURING WATERPROOFING MATERIALS L.L.C

MATERIAL SAFETY DATA SHEET  
R-NOVA 62 ME (WATERPROOFING ACRYLIC COATING)  
REVIEW DATE: 13 June 2019

1) **GENERAL:**

**Product Name:** R-NOVA 62 ME  
**Application Field:** Construction Industry  
**Product Usage:** Waterproofing Applications  
**Supplier/Manufacturer:** SOPREMA for Manufacturing Waterproofing Materials L.L.C  
P.O.Box: 39196 Abu Dhabi, United Arab Emirates.  
Tel +97125503383 / Fax: 97125503382  
[www.soprema.ae](http://www.soprema.ae)

**Issue Date:** 13 June, 2019

2) **INGREDIENTS COMPOSITION:**

Composition	CAS Number	Content %
Acrylic Mixture	Not Listed	< 40
Water	7732-18-5	< 10
Limestone	471-34-1	< 20
Titanium Dioxide	13463-67-7	< 5
Talc	8008-20-6	< 5

3) **POTENTIAL HAZARDS:**

- **Eye contact :** Avoid direct contact with eye. Irritation and cause burning.
- **Skin contact :** Skin irritation upon prolonged contact. However, wear protective gloves.
- **Inhalation :** May be harmful if swallowed. May cause gastric distress, vomiting and diarrhea.

4) **FIRST AID MEASURES:**

- **General :** No major hazard is involved during the use of the **R-NOVA 62 ME** since it is used as cold applied. However, because of its messy nature, wearing proper attire is recommended. Cleaned by gentle rubbing with water.
- **Eye contact :** Irrigate with clean water and consult a physician.
- **Skin contact :** Clean with water, or when dry by Kerosene.
- **Inhalation :** In the event of discomfort as a result of inhalation, move person to fresh air in a well-ventilated area.
- **Swallowing :** If swallowed, no major harm is expected for small portions. Do not induce vomiting

5) **PHYSICAL / CHEMICAL PROPERTIES:**

- **Appearance :** White liquid emulsion
- **Odour :** Mild odor
- **Flash Point :** About 50°C
- **Storage Temperature :** 5 to 30 °C.
- **Specific Gravity :** About 1.3



SOPREMA FOR MANUFACTURING WATERPROOFING MATERIALS L.L.C

---

MATERIAL SAFETY DATA SHEET  
R-NOVA 62 ME (WATERPROOFING ACRYLIC COATING)  
REVIEW DATE: 13 June 2019

---

**6) STABILITY AND REACTIVITY:**

Reactivity : Stable, Reacts with substances which are incompatible with water.

Conditions to avoid: Do not keep the containers open to avoid drying of the product, always keep the lid closed.

**7) TOXICOLOGICAL PROPERTIES:**

No available data.

**8) ECOLOGICAL INFORMATION:**

9) No available data.

**10) FIRE FIGHTING MEASURES:**

- Flammability: Not Combustible
- Extinguishing Media: Carbon Dioxide (CO<sub>2</sub>), Foam or dry chemical may be used. Water may be used to cool containers exposed to heat
- Recommendations: No special recommendation.

**11) ACCIDENTAL RELEASE MEASURES:**

Material may be slippery when spilled. Walk cautiously. Contain and/or absorb spill with inert material (Eg: Sand, Soil). Collect and dispose in accordance with applicable local regulations.

**12) HANDLING AND STORAGE:**

**Handling:** No special handling recommendation. However, proper safety procedures should be taken when lifting heavy drums not to injure workers back and muscles.

**Storage:** Storing in a covered area and not under direct sun heat, spark and flames. Storage temperature is between 5 – 30°C. Store in a neat arrangement, not to block the way in case of store fire.

**Shelf Life:** 12 months if stored according to instructions.

**13) EXPOSURE CONTROLS/PERSONAL PROTECTION:**

No special protection recommendation is applicable.

**14) TRANSPORTATION INFORMATION:**

Hazardous Class: Not Applicable, **HS CODE NO:** 39069000, **UN #** Not Applicable

**15) REGULATORY INFORMATION:**

No regulatory precautions are applicable for this product.

**16) OTHER INFORMATION:**

Only specialized and trained workers should apply this product.