

RESISTO

SUPER ROOF REPAIR - LOW TEMPERATURE

MASTIC



A versatile mastic formulation suitable for low temperature application. It is used to seal flashings, vents, upstands and other roof components, as well as to repair various joints, holes and cracks. In addition, the metal container may be heated to facilitate the application in cold weather.

- Application on dry or wet surfaces, even in cold weather
- Excellent resistance to temperature variations
- Use without primer

PRODUCT PURPOSE

| | | |
|---------------|---------------|------------------|
| Application | Waterproofing | |
| Building Part | Roofing | Foundations |
| | Walls | Other |
| Substrates | Wood | Asphalt shingles |
| | Concrete | Metal |

PRODUCT CHARACTERISTICS

| | |
|-----------------------|------------------------------------|
| Installation Method | Trowel |
| Operating Temperature | -40 °C to 80 °C (-40 °F to 176 °F) |

PACKAGING

| Code | Containers | Quantity per Pallet |
|-------|---------------|---------------------|
| 53016 | 20 kg (44 lb) | 36 |

PROPERTIES


| Properties | SUPER ROOF REPAIR - LOW TEMPERATURE |
|------------------|-------------------------------------|
| Color | Black |
| Solids by Weight | 80.8% |
| Flow | None at these temperatures |

All values are nominal)

Meets or exceeds the requirements of CAN/CGSB-37.5M89 standard.

SUPER ROOF REPAIR - LOW TEMPERATURE

INSTALLATION

| | |
|---------------------------------|---|
| Storage | Two years in its original closed packaging, in a cool, well-ventilated area. Store in a cool, dry place up to 40 °C (104 ° F). The product can withstand freezing. |
| Minimum Application Temperature | -10 °C (14 °F) to 10°C (50°F). The product must be at a minimum temperature of 10°C (50°F) before application. |
| Tools Required |  Trowel |
| Surface Preparation | The substrate must be clean and free of dust, grease or other contaminants. |
| Installation | Apply with a trowel. |
| Drying time | Between 4 and 24 hours, depending on ambient temperature and the amount applied. |
| Recommendations/ Limitations | Do not apply strips greater than 1 cm (1/2 in) in width. It is not recommended to use a product containing bitumen directly on softwood boards or on flexible polyvinyl chloride. |
| Warnings | Keep out of the reach of children. Properly close the container after each use. Keep out of the sun and away from ignition sources. During use, keep away from ignition sources. No smoking. After application, keep away from flames until solvent has evaporated. Do not pour residues in drains. |

