

RESISTO

SUPREME ROOF REPAIR - LOW TEMPERATURE

MASTIC



A superior plastic cement developed specifically for professional roofers. The LOW TEMPERATURE version contains additives enabling it to maintain its flexibility for applications at temperatures below 0 °C (32 °F). In addition, the metal container may be heated to facilitate the application in extreme cold.

- Application on all surfaces with optimum bonding
- Application even in cold weather
- Use without primer

PRODUCT PURPOSE

Application	Waterproofing	
Building Part	Roofing	Foundations
	Walls	Other
Substrates	Wood	Asphalt shingles
	Concrete	Metal

PRODUCT CHARACTERISTICS

Installation Method	Extruder	Trowel
Operating Temperature	-40 °C to 80 °C (-40 °F to 176 °F)	

PACKAGING

Code	Containers	Quantity per Pallet
53024	13.6 kg (30 lb)	48
53025	20 kg (44 lb)	36

PROPERTIES


Properties	SUPREME ROOF REPAIR - LOW TEMPERATURE
Color	Black
Solids by Weight	82.1%
Flow	None at these temperatures

All values are nominal)

Meets or exceeds the requirements of CAN/CGSB-37.5M89 standard.

SUPREME ROOF REPAIR - LOW TEMPERATURE

INSTALLATION

Storage	Two years in its original closed packaging, in a cool, well-ventilated area. Store in a cool, dry place up to 40 °C (104 °F). The product can withstand freezing.
Minimum Application Temperature	-20 °C (14 °F) to 10°C (50°F). The product must be at a minimum temperature of 10°C (50°F) before application.
Tools Required	 Trowel
Surface Preparation	The substrate must be clean and free of dust, grease or other contaminants.
Installation	Apply with a trowel.
Drying time	Between 4 and 24 hours, depending on ambient temperature and the amount applied.
Recommendations/ Limitations	Do not apply strips greater than 1 cm (1/2 in) in width. It is not recommended to use a product containing bitumen directly on softwood boards or on flexible polyvinyl chloride.
Warnings	Keep out of the reach of children. Properly close the container after each use. During use, keep away from ignition sources. No smoking. After application, keep away from flames until solvent has evaporated. Do not pour residues in drains.

