



DESCRIPTION

ELASTOCOL 500 is a primer made from bitumen, fast-evaporating solvents and adhesive enhancing additives. It is required to prime most surfaces such as concrete and metal substrates in order to improve the adhesion of torch-applied waterproofing membranes.

APPLICATION

ELASTOCOL 500 can be applied with a brush, roller or sprayer. It must be thoroughly dry before applying the waterproofing membrane.

WARNING: DO NOT ACCELERATE DRYING OF ELASTOCOL 500 BY HEATING IT WITH A TORCH.

Amount used could increase depending on porosity of the surface.

FOR COMPLETE INFORMATION ON PRODUCT INSTALLATION, PLEASE CONSULT YOUR SOPREMA REPRESENTATIVE.

PROPERTIES

ELASTOCOL 500 meets the requirements of the ASTM D41 standard.

Properties	Standards	ELASTOCOL 500
Specific Gravity at 20 °C	-	1.00 kg/L
Colour	-	Black
Solids by Weight	-	35 %
Viscosity, Brookfield at 25 °C	-	50 cP
Drying time	-	1 to 12 hours

(All values are nominal)

PACKAGING

19 L pails, 200 L drums and 350g spray cans.

Average coverage: 0.15 to 0.25 L/m².

Shelf life: Up to 5 years in original sealed containers, in cool and ventilated area.

CLEANING

Tools can be cleaned with petroleum solvents such as mineral spirits, varsol, xylene, etc.

PARTICULAR INDICATIONS

ELASTOCOL 500 is a flammable product.

Store away from direct sunlight and open flame. Keep ignition sources away during application and until solvent has evaporated.

Harmful if inhaled, swallowed or when in contact with the skin. In closed area, ventilate carefully using mechanical means if necessary.

Do not pour residues in drains.

CONSULT THE MATERIAL SAFETY DATA SHEET PRIOR TO USE.



ELASTOCOL



WATERPROOFING
COMPLEMENTARY PRODUCTS

APPLICATIONS

PRIMER

ELASTOCOL 500

TECHNICAL DATA SHEET ANZ-TDS-24-ELASTOCOL 500

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this publication is based on the present state of our best knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by Commonwealth or State Legislation. The owner, their representative or the contractor is responsible for checking the suitability of products for their intended use.

Note: Field service where provided, does not constitute supervisory responsibility. Suggestions made by Soprema Australia Pty Ltd either verbally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not Soprema Australia Pty Ltd are responsible for carrying out procedures appropriate to a specific application.

DOCUMENT CONTROL	
Product	ELASTOCOL 500
Initial Issue	29.10.2019
Amendment	
Author	JJ

