



WATERPROOFING

APPLICATIONS

WALLS

SOPRASEAL MESH

TECHNICAL DATA SHEET

APTDS-E-161-01

DESCRIPTION

SOPRASEAL MESH is a reinforced non-woven polyester fabric. It is used for above-grade applications with SOPRASEAL LM 202 VP or SOPRASEAL LM 203. SOPRASEAL MESH reinforces SOPRASEAL LM 202 VP or SOPRASEAL LM 203 over acceptable rough openings, sheathing joints and transitions.

APPLICATION

Apply SOPRASEAL LM 202 VP or SOPRASEAL LM 203 to all sheathing joints, terminations, inside and outside corners and rough openings. Immediately place and center SOPRASEAL MESH over wet SOPRASEAL LM 202 VP or SOPRASEAL LM 203, embedding and completely saturating SOPRASEAL MESH. Ensure SOPRASEAL MESH extends evenly on both sides of the sheathing joint. Lap a minimum of 64 mm (2 1/2") of SOPRASEAL MESH at intersections. When product is applied with a roller, allow to dry to touch, before applying SOPRASEAL LM 202 VP or SOPRASEAL LM 203 to entire wall surface. When product is spay applied, "wet on wet" application is acceptable.

LIMITATIONS

Protect SOPRASEAL MESH during transportation and installation to avoid physical damage.

FOR COMPLETE INFORMATION ON PRODUCT INSTALLATION, PLEASE CONSULT YOUR SOPREMA REPRESENTATIVE.

PACKAGING

	SOPRASEAL MESH
Dimensions	100 mm (4 in) / 55 m (180 ft) 150 mm (6 in) / 55 m (180 ft) 230 mm (9 in) / 55 m (180 ft)
Weight	83 g/m ² (2.45 oz/yd ²)

(All values are nominal)

STORAGE AND HANDLING

Store SOPRASEAL MESH in a cool, dry place, and protect from moisture.

