



WATERPROOFING

APPLICATIONS

ROOFS

PARKING DECKS

BALCONIES

ALSAN TRAFIK HP COLORANT

TECHNICAL DATA SHEET

ANZ-TDS-57-ALSAN TRAFIK HP COLORANT

DESCRIPTION

ALSAN TRAFIK HP COLORANT is a pigment paste. When added to ALSAN TRAFIK HP 540, it increases its opacity and widens the possibilities of the ALSAN TRAFIK HP 500 system when it comes to final color.

When added to the ALSAN TRAFIK HP 540 the ALSAN TRAFIK HP COLORANT can also be used to draw lines and delimit certain areas.

INSTALLATION PROCEDURE

MIXING:

- Add the full content of ALSAN TRAFIK HP COLORANT in a 19 L pail of ALSAN TRAFIK HP 540. Mix well for at least 1 minute using a mixer at low speed (300-450 rpm) and a "Jiffy" mixing paddle to ensure color uniformity.

Traffic is allowed 72 hours after the installation of the coloured layer whatever the application.

FOR COMPLETE INFORMATION ON PRODUCT INSTALLATION, PLEASE CONSULT YOUR SOPREMA REPRESENTATIVE.

PACKAGING

SPECIFICATIONS	ALSAN TRAFIK HP COLORANT
Physical state	Coloured liquid paste
Colour	See colour chart ¹
Specific gravity @ 25 °C	0.9 - 1.6 (kg/L)

(All values are nominal)

¹ Colour chart



Grey
Product code:
30136
RAL 7040



Dark Grey
Product code:
30137
RAL 7011



Pebble Grey
Product code:
30139
RAL 7032



Trafik White
Product code:
30140
RAL 9003



Trafik Blue
Product code:
30142
RAL 5005



Black
Product code:
30143
RAL 9017

CLEANING

Tools can be cleaned with petroleum solvents such as mineral spirits, Varsol, Xylene, etc.

STORAGE AND HANDLING

Shelf life: 24 to 60 months in original sealed containers.

ALSAN TRAFIK HP COLORANT must be kept away from heat, humidity or direct sunlight. Store in a cool and dry area. Use in a well ventilated area, far from any open flame. Avoid breathing solvent vapours and prolonged skin contact.

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this publication is based on the present state of our best knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by Commonwealth or State Legislation. The owner, their representative and/or the contractor are responsible for checking the suitability of products for their intended use.



SOPREMA.COM.AU • +61 (3) 9221 6230

TDS_ALSAN_TRAFIK_HP_COLORANT_11-2020

1/1